


Amphenol LTW
安費諾亮泰企業股份有限公司

		2	3	4	5	6	7	8
F								
Ordering Information:								
BX-0XBFXA-QL8XXX								
Current Rating								
D: 5A								
B: 10A								
Number of Contacts								
5A: 02,03,04,05,06,07,08								
10A: 02,03,04								
Contacts Gender								
M: Male Pin								
F: Female Pin								
S: With Red Color Seal, Cable OD 5.0~6.0mm.								
M: With Yellow Color Seal, Cable OD 6.0~8.0mm.								
L: With Blue Color Seal, Cable OD 8.0~10.0mm.								
E								
Mating Connector:								
Overmolded with Cable: BX-0XAMXM-QL8XXX								
Receptacle: BX-0XXMXS-QX8001								
Field Installable: BX-0XBMXA-QLXXX								
D								
Tool Part No:								
ASST-C-XXA-W-X								
C								
Pin Assignments Front View								
10A ; 300Vac/Vdc 2 Contacts(02)								
10A ; 300Vac/Vdc 3 Contacts(03)								
10A ; 300Vac/Vdc 4 Contacts(04)								
5A ; 300Vac/Vdc 2 Contacts(02)								
5A ; 300Vac/Vdc 3 Contacts(03)								
5A ; 300Vac/Vdc 4 Contacts(04)								
5A ; 300Vac/Vdc 5 Contacts(05)								
5A ; 300Vac/Vdc 6 Contacts(06)								
5A ; 300Vac/Vdc 7 Contacts(07)								
5A ; 300Vac/Vdc 8 Contacts(08)								
Male Pin								
Female Pin								
B								
UNIT: mm								
TOLERANCE								
±0.5 mm								
A								
TITLE X-Lok B-Size Field Installable Cable Type F Conn								
SCALE 8:5								
REV. A								
SHEET 2 OF 2								
MC-REV. A.3								
QC: Inspection item								
2								
3								
4								
5								
6								
7								
8								
Amphenol LTW								
安費諾亮泰企業股份有限公司								
DRAWN BY Victor Hung								
CHECKED BY Wes Fan								
APPROVED BY Kevin Hu								
ITEM NO BX-0XBFXA-QL8XXX								
DATE 2016/11/23								
DATE 2016/11/23								
DATE 2016/11/23								
CUSTOMER ALTW								
FMM10702-01-02A1								



Amphenol LTW
安費諾亮泰企業股份有限公司