

Specification Sheet

Part Number: 596-00810

DESCONECTADOR SOLAR

Solar Label, Reflective, Spanish, SOLAR DISCONNECT, 6.5" x 1.0", VL, Red, 50/pkg

Article Number	596-00810
Type	SOLARDS
Color	Red (RD)
Features & Benefits	• Made with UV-stable inks and materials for durability and weather resistance. • Reflective properties to meet applicable NEC code requirements for reflective identification. • Supplied with an aggressive adhesive to ensure long life. Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description	HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Solar Label, Reflective, Spanish, SOLAR DISCONNECT, 6.5" x 1.0", VL, Red, 50/pkg
Global Part Name	SOLARDS-242/552-RD
Technical Description	Pre-Printed Solar Label, Reflective, Spanish Version, "SOLAR DISCONNECT", 6.5" X 1", Red
Local Order Number 2	English Version: 596-00246
Width W (Imperial)	6.5
Width W (Metric)	165.1
Thickness T (Metric)	64.0
Height H (Imperial)	1.0
Height H (Metric)	25.4
Material	Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate
Material Shortcut	242/552

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521
Weight (Imperial)	31.97

