

Part Number: 1201080210

Product Description: Micro-Change(M12) Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male Push/Pull RJ-45, 22 AWG, Shielded PUR Cable, 25.0m (16.40')

Length

Series Number: 120108 Status: Active

Product Category: Circular Industrial Engineering Number: E17A06011M250

Cordsets

Documents & Resources

Drawings

Drawing 1201080210_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Reviewed per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)4144-DC (27 June 2024)
EU RoHS	Not Reviewed per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120108
Description	Micro-Change(M12) Double-Ended Cordset, 4 Poles, D-Coded, Male (Straight) to Male Push/Pull RJ-45, 22 AWG, Shielded PUR Cable, 25.0m (16.40') Length
IP Rating	IP67
Performance Category	5e
Product Family	Brad Industrial Ethernet Solutions
Product Name	Micro-Change (M12)
Region	America, Asia, Europe
Туре	Double Ended
UPC	78172535843

Agency

UL	E200650

Electrical

Current - Maximum per Contact	1.5A
Voltage - Maximum	30V

Physical

	T
Cable Diameter	6.70mm (.264")
Cable Length	25.0m (82.02')
Color - Cable Jacket	Green
Connector End A	Micro-Change (M12)
Connector End B	RJ-45 (standard)
Coupling Style	Threaded
Gender	Male-Male
Keyway	D-Coded
LED Indicator	No
Material - Cable Jacket	PUR
Material - Connector Body	PUR

Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - Plating Mating	Gold
Orientation	Straight to Straight
Poles	4
Temperature Range - Operating	-20° to +60°C
Wire/Cable Type	Shielded PUR
Wire Size (AWG)	22

This document was generated on Sep 16, 2024