

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A1	REVISED PER ECO-11-005294	14APR11	HMR

RECOMMENDED MOUNTING HOLE PATTERN

CAPTURED CENTER CONTACT

ELECTRICAL	MECHANICAL	ENVIRONMENTAL	HOUSING	BRASS, PER ASTM-B-16 HALF HARD		NICKEL PLATE PER QQ-N-290			
Nominal Impedance (Ohms) <u>50</u>	Force to Engage: (Lbs) <u>3.4 MAX</u>	Temperature Rating <u>-65°C to +165°C</u>	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457		N/A			
Frequency Range (GHz) <u>DC TO 6.0</u>	Force to Disengage: (Lbs) <u>1.77 MIN - 4.5 MAX</u>	Vibration <u>MIL-STD-202, Method 204, Condition B</u>	CENTER CONTACT	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H		GOLD PLATE PER MIL-G-45204			
Voltage Rating (VRMS MAX) <u>335 @ Sea level</u>	Center Contact Captivation: <u>Axial 4.5lbs @ 1 minute with .006" displacement</u>	Thermal shock <u>MIL-STD-202, Method 107, Condition B</u>	COMPONENT	MATERIAL		FINISH			
VSWR <u>N/A</u>	<u>XX.XX = mm</u> <u>.XXX = in</u>	Moisture Resistance <u>MIL-STD-202, Method 106</u>	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCE ON DEC ANGLES ±0.13 ± 1°	DRAWN BY <u>K.C.MAHER</u> DATE <u>10/18/90</u>					
Insertion Loss <u>N/A</u>		Corrosion <u>MIL-STD-202, Method 101, Condition B, 48 Hrs</u>		CHECKED BY <u>M.Y.</u> <u>10-19-90</u>					
Corona, 70,000 Ft (VRMS MIN) <u>250</u>				APPD BY <u>Q.R.</u> <u>10-19-90</u>	TITLE OSX PRINTED WIRING BOARD JACK RECEPTACLE STRAIGHT TERMINAL				
D.W.V. (VRMS MIN) <u>1000</u>				USE ASS'Y PROCEDURE N/A NO. AP _____	SIZE B	CODE IDENT NO. 26805	REV A1		
Contact Resistance				CUSTOMER DRAWING	SCALE 5 : 1	1060985-1	SHEET 1 OF 1		
Center Contact (Milliohms MAX) <u>5.0</u>									
Outer Contact (Milliohms MAX) <u>10</u>									
RF High Potential (VRMS MIN @ 5 MHz) <u>670</u>									
I.R. (Megohms Min) <u>10,000</u>									

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[5862-5002-10](#)