



Part Number : [2018431040](#)
Product Description : MultiCat High-Power Right-Angle Header, 4 Circuits, Key A, Black
Series Number : 201843
Status : Active
Product Category : PCB Headers and Receptacles
Engineering Number : 2018431040-FCT



Documents & Resources

Drawings

[2018431040_sd.pdf](#)
[2018420000-PK-000.pdf](#)

3D Models and Design Files

[2018431040_stp.zip](#)
[SYM-201843-1040-001.zip](#)

Specifications

[2018400000-AS-000.pdf](#)
[2018400000-PS-000.pdf](#)
[2018400000-TS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 34; 3; 44; 33
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	201843
Description	MultiCat High-Power Right-Angle Header, 4 Circuits, Key A, Black
Application	Power, Wire-to-Board
Component Type	PCB Header
Product Name	MultiCat
UPC	889056747646

Agency

UL	E29179
----	--------

Electrical

Current - Maximum per Contact	40.0A
Voltage - Maximum	1000V AC/DC

Physical

Breakaway	No
Circuits (Loaded)	4
Circuits (maximum)	4
Color - Resin	Black

Durability (mating cycles max)	500
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	PEI
Net Weight	14.631/g
Number of Rows	1
Orientation	Right Angle
Packaging Type	Tray
PCB Thickness - Recommended	2.50mm
Pitch - Mating Interface	7.40mm
Plating min - Mating	0.102µm
Plating min - Termination	5.080µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Yes
Temperature Range - Operating	-40° to +150°C
Termination Interface Style	Through Hole

Mates With / Use With

Mates with Part(s)

Description	Part Number
MultiCat-to-MultiCat High-Power Off-the-Shelf (OTS) Cable Assembly, Female, Single Row, 300.00mm Length, 8 AWG, 4 Circuits, Key A, Black	<u>451410401</u>
MultiCat-to-MultiCat High-Power Off-the-Shelf (OTS) Cable Assembly, Female, Single Row, 1.0m Length, 8 AWG, 4 Circuits, Key A, Black	<u>451410410</u>

MultiCat High-Power Inline Receptacle Housings	<u>201841</u>
---	---------------