

## DC Film Capacitors MKT Radial Potted Type





### FEATURES

- AEC-Q200 qualified (rev. D) for PCM  $\leq 27.5$  mm (for larger available components on request)
- High temperature capabilities, up to 150 °C
- Capacitance up to 560  $\mu$ F
- 4-pin version available under request for pitch  $\geq 37.5$  mm, under request
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

### APPLICATIONS



- Automotive
- DC filtering
- Low voltage DC link




| QUICK REFERENCE DATA                            |                                                                                                                                                                                                                                                  |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Capacitance range                               | 1000 pF to 560 $\mu$ F                                                                                                                                                                                                                           |
| Capacitance tolerance                           | $\pm 20$ %, $\pm 10$ %, $\pm 5$ %                                                                                                                                                                                                                |
| Climatic testing class according to IEC 60068-1 | 55/125/56                                                                                                                                                                                                                                        |
| Maximum application temperature                 | 125 °C                                                                                                                                                                                                                                           |
| Reference standards                             | IEC 60384-2                                                                                                                                                                                                                                      |
| Dielectric                                      | Polyester film                                                                                                                                                                                                                                   |
| Electrodes                                      | Metallized                                                                                                                                                                                                                                       |
| Construction                                    | <p>Mono construction</p>  <p>Series construction (630 V and 1000 V)</p>  |
| Encapsulation                                   | Plastic case, epoxy resin sealed, flame retardant UL-class 94 V-0                                                                                                                                                                                |
| Leads                                           | Tinned wire                                                                                                                                                                                                                                      |
| Marking                                         | C-value; tolerance; rated voltage; code for dielectric material; code for manufacturing origin; manufacturer's type designation; manufacturer's logo or name; year and week of manufacture                                                       |
| Rated (DC) voltage                              | 63 V <sub>DC</sub> , 100 V <sub>DC</sub> , 160 V <sub>DC</sub> , 250 V <sub>DC</sub> , 400 V <sub>DC</sub> , 630 V <sub>DC</sub> , 1000 V <sub>DC</sub>                                                                                          |
| Rated (AC) voltage                              | 40 V <sub>AC</sub> , 63 V <sub>AC</sub> , 160 V <sub>AC</sub> , 200 V <sub>AC</sub> , 220 V <sub>AC</sub>                                                                                                                                        |
| Maximum operating temperature for limited time  | 150 °C at 0.3 U <sub>R</sub> for maximum 200 h (not applicable for pitch $\geq 37.5$ mm)                                                                                                                                                         |

### Note

- For more detailed data and test requirements, contact [dc-film@vishay.com](mailto:dc-film@vishay.com)

| DIMENSIONS in millimeters                                                                                                                                                |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|   |

**COMPOSITION OF CATALOG NUMBER**

**Notes**

- For detailed tape specifications refer to packaging information [www.vishay.com/docs?28139](http://www.vishay.com/docs?28139) or end of catalog
- For PCM  $\geq 37.5$  mm, 4 pin versions are available under customer request

| SPECIFIC REFERENCE DATA                                                                           |                                                           |                     |                     |                                |                           |                           |                           |
|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------|---------------------|---------------------|--------------------------------|---------------------------|---------------------------|---------------------------|
| DESCRIPTION                                                                                       |                                                           |                     |                     | VALUE                          |                           |                           |                           |
| Tangent of loss angle:                                                                            |                                                           |                     |                     | at 100 Hz                      | at 1 kHz                  | at 10 kHz                 | at 100 kHz                |
| $C \leq 0.1 \mu\text{F}$                                                                          |                                                           |                     |                     | -                              | $\leq 80 \times 10^{-4}$  | $\leq 150 \times 10^{-4}$ | $\leq 250 \times 10^{-4}$ |
| $0.1 \mu\text{F} < C \leq 1.0 \mu\text{F}$                                                        |                                                           |                     |                     | -                              | $\leq 80 \times 10^{-4}$  | $\leq 150 \times 10^{-4}$ | -                         |
| $1.0 \mu\text{F} < C \leq 10.0 \mu\text{F}$                                                       |                                                           |                     |                     | $\leq 35 \times 10^{-4}$       | $\leq 150 \times 10^{-4}$ | -                         | -                         |
| $10.0 \mu\text{F} < C \leq 100 \mu\text{F}$                                                       |                                                           |                     |                     | $\leq 50 \times 10^{-4}$       | $\leq 300 \times 10^{-4}$ | -                         | -                         |
| $C > 100 \mu\text{F}$                                                                             |                                                           |                     |                     | $\leq 70 \times 10^{-4}$       | -                         | -                         | -                         |
| PITCH (mm)                                                                                        | MAXIMUM PULSE RISE TIME (dU/dt) <sub>R</sub> [V/ $\mu$ s] |                     |                     |                                |                           |                           |                           |
|                                                                                                   | 63 V <sub>DC</sub>                                        | 100 V <sub>DC</sub> | 160 V <sub>DC</sub> | 250 V <sub>DC</sub>            | 400 V <sub>DC</sub>       | 630 V <sub>DC</sub>       | 1000 V <sub>DC</sub>      |
| 10                                                                                                | 12                                                        | 18                  | -                   | 36                             | 52                        | 70                        | 260                       |
| 15                                                                                                | 8                                                         | 10                  | -                   | 20                             | 32                        | 66                        | 130                       |
| 22.5                                                                                              | 5                                                         | 6                   | -                   | 12                             | 18                        | 38                        | 68                        |
| 27.5                                                                                              | 3                                                         | 5                   | 6                   | 8                              | 14                        | 28                        | 50                        |
| 37.5                                                                                              | 0.8                                                       | 1                   | 2                   | 3                              | -                         | -                         | -                         |
| 52.5                                                                                              | 0.2                                                       | 0.3                 | 0.4                 | 1                              | -                         | -                         | -                         |
| If the maximum pulse voltage is less than the rated voltage higher dU/dt values can be permitted. |                                                           |                     |                     |                                |                           |                           |                           |
| R between leads, for $C \leq 0.33 \mu\text{F}$ and $U_R \leq 100 \text{ V}$                       |                                                           |                     |                     | > 15 000 M $\Omega$            |                           |                           |                           |
| R between leads, for $C \leq 0.33 \mu\text{F}$ and $U_R > 100 \text{ V}$                          |                                                           |                     |                     | > 30 000 M $\Omega$            |                           |                           |                           |
| RC between leads, for $C > 0.33 \mu\text{F}$ and $U_R \leq 100 \text{ V}$                         |                                                           |                     |                     | > 5000 s                       |                           |                           |                           |
| RC between leads, for $C > 0.33 \mu\text{F}$ and $U_R > 100 \text{ V}$                            |                                                           |                     |                     | > 10 000 s                     |                           |                           |                           |
| R between leads and case, 100 V; (foil method)                                                    |                                                           |                     |                     | > 30 000 M $\Omega$            |                           |                           |                           |
| Withstanding (DC) voltage (cut off current 10 mA) <sup>(1)</sup> ; rise time < 1000 V/s           |                                                           |                     |                     | 1.6 x U <sub>RDC</sub> , 1 min |                           |                           |                           |
| Withstanding (DC) leads and case                                                                  |                                                           |                     |                     | 2 x U <sub>RDC</sub> , 1 min   |                           |                           |                           |
| Maximum application temperature                                                                   |                                                           |                     |                     | 125 °C                         |                           |                           |                           |

**Note**

- <sup>(1)</sup> See "Voltage Proof Test for Metalized Film Capacitors": [www.vishay.com/doc?28169](http://www.vishay.com/doc?28169)



| ELECTRICAL DATA         |              |                     |                 |                 |                                                |             |                                  |                                                            |
|-------------------------|--------------|---------------------|-----------------|-----------------|------------------------------------------------|-------------|----------------------------------|------------------------------------------------------------|
| U <sub>RDC</sub><br>(V) | CAP.<br>(μF) | CAPACITANCE<br>CODE | VOLTAGE<br>CODE | V <sub>AC</sub> | DIMENSIONS<br>w x h x l<br>(mm) <sup>(1)</sup> | PCM<br>(mm) | d <sub>t</sub> ± 0.08 mm<br>(mm) | ORDERING CODE FOR 10 %<br>TOL./BULK PACKING <sup>(2)</sup> |
| 63                      | 0.22         | 422                 | 06              | 40              | 3.5 x 8.0 x 13.0                               | 10.0        | 0.80                             | MKT1820422065                                              |
|                         | 0.33         | 433                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820433065                                              |
|                         | 0.47         | 447                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820447065                                              |
|                         | 0.68         | 468                 |                 |                 | 4.0 x 9.0 x 13.0                               | 10.0        |                                  | MKT1820468065                                              |
|                         | 1.0          | 510                 |                 |                 | 4.5 x 9.5 x 13.0                               | 10.0        |                                  | MKT1820510065                                              |
|                         | 1.5          | 515                 |                 |                 | 5.5 x 10.5 x 13.0                              | 10.0        |                                  | MKT1820515065                                              |
|                         | 2.2          | 522                 |                 |                 | 6.5 x 11.5 x 13.0                              | 10.0        |                                  | MKT1820522065                                              |
|                         | 3.3          | 533                 |                 |                 | 9.0 x 15.5 x 13.0                              | 10.0        |                                  | MKT1820533065M                                             |
|                         | 3.3          | 533                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820533065                                              |
|                         | 4.7          | 547                 |                 |                 | 9.0 x 15.5 x 13.0                              | 10.0        |                                  | MKT1820547065M                                             |
|                         | 4.7          | 547                 |                 |                 | 7.5 x 13.5 x 18.0                              | 15.0        |                                  | MKT1820547065                                              |
|                         | 6.8          | 568                 |                 |                 | 8.5 x 14.5 x 18.0                              | 15.0        |                                  | MKT1820568065                                              |
|                         | 10.0         | 610                 |                 |                 | 8.5 x 17.5 x 18.0                              | 15.0        |                                  | MKT1820610065                                              |
|                         | 15.0         | 615                 |                 |                 | 8.5 x 16.5 x 26.5                              | 22.5        |                                  | MKT1820615065                                              |
|                         | 22.0         | 622                 |                 |                 | 10.5 x 18.5 x 26.5                             | 22.5        |                                  | MKT1820622065M                                             |
|                         | 18.0         | 618                 |                 |                 | 9.0 x 19.0 x 32.0                              | 27.5        |                                  | MKT1820618065                                              |
|                         | 22.0         | 622                 |                 |                 | 11.0 x 21.0 x 32.0                             | 27.5        |                                  | MKT1820622065                                              |
|                         | 27.0         | 627                 |                 |                 | 11.0 x 21.0 x 32.0                             | 27.5        |                                  | MKT1820627065                                              |
|                         | 33.0         | 633                 |                 |                 | 13.0 x 23.0 x 32.0                             | 27.5        |                                  | MKT1820633065                                              |
|                         | 39.0         | 639                 |                 |                 | 13.0 x 23.0 x 32.0                             | 27.5        |                                  | MKT1820639065                                              |
|                         | 47.0         | 647                 |                 |                 | 15.0 x 25.0 x 32.0                             | 27.5        |                                  | MKT1820647065                                              |
|                         | 56.0         | 656                 |                 |                 | 18.0 x 28.0 x 32.0                             | 27.5        |                                  | MKT1820656065                                              |
|                         | 68.0         | 668                 |                 |                 | 18.0 x 28.0 x 32.0                             | 27.5        |                                  | MKT1820668065                                              |
|                         | 82.0         | 682                 |                 |                 | 21.0 x 31.0 x 32.0                             | 27.5        |                                  | MKT1820682065                                              |
|                         | 100.0        | 710                 |                 |                 | 21.0 x 31.0 x 32.0                             | 27.5        |                                  | MKT1820710065M                                             |
|                         | 100.0        | 710                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        | 1.0                              | MKT1820710065                                              |
|                         | 120.0        | 712                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820712065                                              |
|                         | 150.0        | 715                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820715065                                              |
|                         | 180.0        | 718                 |                 |                 | 21.5 x 38.5 x 43.0                             | 37.5        |                                  | MKT1820718065                                              |
|                         | 220.0        | 722                 |                 |                 | 24.0 x 44.0 x 42.0                             | 37.5        |                                  | MKT1820722065M                                             |
|                         | 270.0        | 727                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820727065M                                             |
|                         | 330.0        | 733                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820733065M                                             |
|                         | 220.0        | 722                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        | 1.2                              | MKT1820722065                                              |
|                         | 270.0        | 727                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820727065                                              |
|                         | 330.0        | 733                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820733065                                              |
|                         | 390.0        | 739                 |                 |                 | 30.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820739065                                              |
|                         | 470.0        | 747                 |                 |                 | 35.0 x 50.0 x 57.5                             | 52.5        |                                  | MKT1820747065                                              |
|                         | 560.0        | 756                 |                 |                 | 35.0 x 50.0 x 57.5                             | 52.5        |                                  | MKT1820756065                                              |

**Notes**

(1) For tolerances see chapter "Space Requirements for Printed-Circuit Board Applications and Dimension Tolerances"

(2) Please replace "5" by: "4" for 5 % tolerance or "6" for 20 % tolerance



| ELECTRICAL DATA         |              |                     |                 |                 |                                                |             |                                  |                                                            |
|-------------------------|--------------|---------------------|-----------------|-----------------|------------------------------------------------|-------------|----------------------------------|------------------------------------------------------------|
| U <sub>RDC</sub><br>(V) | CAP.<br>(μF) | CAPACITANCE<br>CODE | VOLTAGE<br>CODE | V <sub>AC</sub> | DIMENSIONS<br>w x h x l<br>(mm) <sup>(1)</sup> | PCM<br>(mm) | d <sub>t</sub> ± 0.08 mm<br>(mm) | ORDERING CODE FOR 10 %<br>TOL./BULK PACKING <sup>(2)</sup> |
| 100                     | 0.068        | 368                 | 01              | 63              | 3.5 x 8.0 x 13.0                               | 10.0        | 0.8                              | MKT1820368015                                              |
|                         | 0.10         | 410                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820410015                                              |
|                         | 0.15         | 415                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820415015                                              |
|                         | 0.22         | 422                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820422015                                              |
|                         | 0.33         | 433                 |                 |                 | 4.0 x 9.0 x 13.0                               | 10.0        |                                  | MKT1820433015                                              |
|                         | 0.47         | 447                 |                 |                 | 4.5 x 9.5 x 13.0                               | 10.0        |                                  | MKT1820447015                                              |
|                         | 0.68         | 468                 |                 |                 | 5.5 x 10.5 x 13.0                              | 10.0        |                                  | MKT1820468015                                              |
|                         | 1.0          | 510                 |                 |                 | 5.5 x 10.5 x 13.0                              | 10.0        |                                  | MKT1820510015M                                             |
|                         | 1.0          | 510                 |                 |                 | 5.5 x 10.5 x 18.0                              | 15.0        |                                  | MKT1820510015                                              |
|                         | 1.5          | 515                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820515015                                              |
|                         | 2.2          | 522                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820522015                                              |
|                         | 3.3          | 533                 |                 |                 | 8.5 x 14.5 x 18.0                              | 15.0        |                                  | MKT1820533015                                              |
|                         | 4.7          | 547                 |                 |                 | 8.5 x 14.5 x 18.0                              | 15.0        |                                  | MKT1820547015M                                             |
|                         | 4.7          | 547                 |                 |                 | 7.5 x 15.5 x 26.5                              | 22.5        |                                  | MKT1820547015                                              |
|                         | 6.8          | 568                 |                 |                 | 8.5 x 16.5 x 26.5                              | 22.5        |                                  | MKT1820568015                                              |
|                         | 10.0         | 610                 |                 |                 | 10.5 x 18.5 x 26.5                             | 22.5        |                                  | MKT1820610015                                              |
|                         | 15.0         | 615                 |                 |                 | 10.5 x 18.5 x 26.5                             | 22.5        |                                  | MKT1820615015M                                             |
|                         | 15.0         | 615                 |                 |                 | 11.0 x 21.0 x 32.0                             | 27.5        |                                  | MKT1820615015                                              |
|                         | 18.0         | 618                 |                 |                 | 13.0 x 23.0 x 32.0                             | 27.5        |                                  | MKT1820618015                                              |
|                         | 22.0         | 622                 |                 |                 | 13.0 x 23.0 x 32.0                             | 27.5        |                                  | MKT1820622015                                              |
|                         | 27.0         | 627                 |                 |                 | 15.0 x 25.0 x 32.0                             | 27.5        |                                  | MKT1820627015                                              |
|                         | 33.0         | 633                 |                 |                 | 18.0 x 28.0 x 32.0                             | 27.5        |                                  | MKT1820633015                                              |
|                         | 39.0         | 639                 |                 |                 | 18.0 x 28.0 x 32.0                             | 27.5        |                                  | MKT1820639015                                              |
|                         | 47.0         | 647                 |                 |                 | 21.0 x 31.0 x 32.0                             | 27.5        |                                  | MKT1820647015                                              |
|                         | 56.0         | 656                 |                 |                 | 21.0 x 31.0 x 32.0                             | 27.5        |                                  | MKT1820656015M                                             |
|                         | 56.0         | 656                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        | 1.0                              | MKT1820656015                                              |
|                         | 68.0         | 668                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820668015                                              |
|                         | 82.0         | 682                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820682015                                              |
|                         | 100.0        | 710                 |                 |                 | 21.5 x 38.5 x 43.0                             | 37.5        |                                  | MKT1820710015                                              |
|                         | 120.0        | 712                 |                 |                 | 24.0 x 44.0 x 42.0                             | 37.5        |                                  | MKT1820712015M                                             |
|                         | 150.0        | 715                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820715015M                                             |
|                         | 180.0        | 718                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820718015M                                             |
|                         | 120.0        | 712                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        | 1.2                              | MKT1820712015                                              |
|                         | 150.0        | 715                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820715015                                              |
|                         | 180.0        | 718                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820718015                                              |
|                         | 220.0        | 722                 |                 |                 | 30.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820722015                                              |
|                         | 270.0        | 727                 |                 |                 | 35.0 x 50.0 x 57.5                             | 52.5        |                                  | MKT1820727015                                              |
|                         | 330.0        | 733                 |                 |                 | 35.0 x 50.0 x 57.5                             | 52.5        |                                  | MKT1820733015                                              |

**Notes**

<sup>(1)</sup> For tolerances see chapter "Space Requirements for Printed-Circuit Board Applications and Dimension Tolerances"

<sup>(2)</sup> Please replace "5" by: "4" for 5 % tolerance or "6" for 20 % tolerance



| ELECTRICAL DATA         |              |                     |                 |                 |                                                |             |                                  |                                                            |
|-------------------------|--------------|---------------------|-----------------|-----------------|------------------------------------------------|-------------|----------------------------------|------------------------------------------------------------|
| U <sub>RDC</sub><br>(V) | CAP.<br>(μF) | CAPACITANCE<br>CODE | VOLTAGE<br>CODE | V <sub>AC</sub> | DIMENSIONS<br>w x h x l<br>(mm) <sup>(1)</sup> | PCM<br>(mm) | d <sub>t</sub> ± 0.08 mm<br>(mm) | ORDERING CODE FOR 10 %<br>TOL./BULK PACKING <sup>(2)</sup> |
| 160                     | 4.7          | 547                 | 16              | 63              | 9.0 x 19.0 x 32.0                              | 27.5        | 0.8                              | MKT1820547165                                              |
|                         | 6.8          | 568                 |                 |                 | 11.0 x 21.0 x 32.0                             | 27.5        |                                  | MKT1820568165                                              |
|                         | 10.0         | 610                 |                 |                 | 11.0 x 21.0 x 32.0                             | 27.5        |                                  | MKT1820610165                                              |
|                         | 15.0         | 615                 |                 |                 | 13.0 x 23.0 x 32.0                             | 27.5        |                                  | MKT1820615165                                              |
|                         | 18.0         | 618                 |                 |                 | 15.0 x 25.0 x 32.0                             | 27.5        |                                  | MKT1820618165                                              |
|                         | 22.0         | 622                 |                 |                 | 18.0 x 28.0 x 32.0                             | 27.5        |                                  | MKT1820622165                                              |
|                         | 27.0         | 627                 |                 |                 | 18.0 x 28.0 x 32.0                             | 27.5        |                                  | MKT1820627165                                              |
|                         | 33.0         | 633                 |                 |                 | 31.0 x 31.0 x 32.0                             | 27.5        |                                  | MKT1820633165M                                             |
|                         | 33.0         | 633                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        | 1.0                              | MKT1820633165                                              |
|                         | 39.0         | 639                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820639165                                              |
|                         | 47.0         | 647                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820647165                                              |
|                         | 56.0         | 656                 |                 |                 | 21.5 x 38.5 x 43.0                             | 37.5        |                                  | MKT1820656165                                              |
|                         | 68.0         | 668                 |                 |                 | 21.5 x 38.5 x 43.0                             | 37.5        |                                  | MKT1820668165                                              |
|                         | 82.0         | 682                 |                 |                 | 24.0 x 44.0 x 42.0                             | 37.5        |                                  | MKT1820682165M                                             |
|                         | 100.0        | 710                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820710165M                                             |
|                         | 120.0        | 712                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820712165M                                             |
|                         | 82.0         | 682                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        | 1.2                              | MKT1820682165                                              |
|                         | 100.0        | 710                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820710165                                              |
|                         | 120.0        | 712                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820712165                                              |
|                         | 150.0        | 715                 |                 |                 | 30.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820715165                                              |
|                         | 180.0        | 718                 |                 |                 | 35.0 x 50.0 x 57.5                             | 52.5        |                                  | MKT1820718165                                              |
|                         | 220.0        | 722                 |                 |                 | 35.0 x 50.0 x 57.5                             | 52.5        |                                  | MKT1820722165                                              |
| 250                     | 0.022        | 322                 | 25              | 160             | 3.5 x 8.0 x 13.0                               | 10.0        | 0.8                              | MKT1820322255                                              |
|                         | 0.033        | 333                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820333255                                              |
|                         | 0.047        | 347                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820347255                                              |
|                         | 0.068        | 368                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820368255                                              |
|                         | 0.10         | 410                 |                 |                 | 4.5 x 9.5 x 13.0                               | 10.0        |                                  | MKT1820410255                                              |
|                         | 0.15         | 415                 |                 |                 | 5.5 x 10.5 x 13.0                              | 10.0        |                                  | MKT1820415255                                              |
|                         | 0.22         | 422                 |                 |                 | 6.5 x 11.5 x 13.0                              | 10.0        |                                  | MKT1820422255                                              |
|                         | 0.33         | 433                 |                 |                 | 6.5 x 11.5 x 13.0                              | 10.0        |                                  | MKT1820433255M                                             |
|                         | 0.33         | 433                 |                 |                 | 5.5 x 10.5 x 18.0                              | 15.0        |                                  | MKT1820433255                                              |
|                         | 0.47         | 447                 |                 |                 | 9.0 x 15.5 x 13.0                              | 10.0        |                                  | MKT1820447255M                                             |
|                         | 0.47         | 447                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820447255                                              |
|                         | 0.68         | 468                 |                 |                 | 7.5 x 13.5 x 18.0                              | 15.0        |                                  | MKT1820468255                                              |
|                         | 1.0          | 510                 |                 |                 | 8.5 x 14.5 x 18.0                              | 15.0        |                                  | MKT1820510255                                              |
|                         | 1.5          | 515                 |                 |                 | 10.5 x 17.5 x 18.0                             | 15.0        |                                  | MKT1820515255M                                             |
|                         | 1.5          | 515                 |                 |                 | 8.5 x 16.5 x 26.5                              | 22.5        |                                  | MKT1820515255                                              |
|                         | 2.2          | 522                 |                 |                 | 10.5 x 18.5 x 26.5                             | 22.5        |                                  | MKT1820522255                                              |
|                         | 3.3          | 533                 |                 |                 | 12.5 x 20.0 x 26.5                             | 22.5        |                                  | MKT1820533255                                              |

## Notes

(1) For tolerances see chapter "Space Requirements for Printed-Circuit Board Applications and Dimension Tolerances"

(2) Please replace "5" by: "4" for 5 % tolerance or "6" for 20 % tolerance



| ELECTRICAL DATA         |              |                     |                 |                 |                                                |             |                                  |                                                            |
|-------------------------|--------------|---------------------|-----------------|-----------------|------------------------------------------------|-------------|----------------------------------|------------------------------------------------------------|
| U <sub>RDC</sub><br>(V) | CAP.<br>(μF) | CAPACITANCE<br>CODE | VOLTAGE<br>CODE | V <sub>AC</sub> | DIMENSIONS<br>w x h x l<br>(mm) <sup>(1)</sup> | PCM<br>(mm) | d <sub>t</sub> ± 0.08 mm<br>(mm) | ORDERING CODE FOR 10 %<br>TOL./BULK PACKING <sup>(2)</sup> |
| 250                     | 4.7          | 547                 | 25              | 100             | 11.0 x 21.0 x 32.0                             | 27.5        | 0.8                              | MKT1820547255                                              |
|                         | 6.8          | 568                 |                 |                 | 13.0 x 23.0 x 32.0                             | 27.5        |                                  | MKT1820568255                                              |
|                         | 10.0         | 610                 |                 |                 | 15.0 x 25.0 x 32.0                             | 27.5        |                                  | MKT1820610255                                              |
|                         | 15.0         | 615                 |                 |                 | 18.0 x 28.0 x 32.0                             | 27.5        |                                  | MKT1820615255                                              |
|                         | 18.0         | 618                 |                 |                 | 21.0 x 31.0 x 32.0                             | 27.5        |                                  | MKT1820618255M                                             |
|                         | 18.0         | 618                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        | 1.0                              | MKT1820618255                                              |
|                         | 22.0         | 622                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820622255                                              |
|                         | 27.0         | 627                 |                 |                 | 18.5 x 35.5 x 43.0                             | 37.5        |                                  | MKT1820627255                                              |
|                         | 33.0         | 633                 |                 |                 | 21.5 x 38.5 x 43.0                             | 37.5        |                                  | MKT1820633255                                              |
|                         | 39.0         | 639                 |                 |                 | 21.5 x 38.5 x 43.0                             | 37.5        |                                  | MKT1820639255                                              |
|                         | 47.0         | 647                 |                 |                 | 24.0 x 44.0 x 42.0                             | 37.5        | 1.2                              | MKT1820647255                                              |
|                         | 56.0         | 656                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820656255M                                             |
|                         | 68.0         | 668                 |                 |                 | 30.0 x 45.0 x 42.0                             | 37.5        |                                  | MKT1820668255M                                             |
|                         | 56.0         | 656                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820656255                                              |
|                         | 68.0         | 668                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820668255                                              |
|                         | 82.0         | 682                 |                 |                 | 25.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820682255                                              |
|                         | 100.0        | 710                 |                 |                 | 30.0 x 45.0 x 57.5                             | 52.5        |                                  | MKT1820710255                                              |
|                         | 120.0        | 712                 |                 |                 | 35.0 x 50.0 x 57.5                             | 52.5        |                                  | MKT1820712255                                              |
| 400                     | 0.010        | 310                 | 40              | 200             | 3.5 x 8.0 x 13.0                               | 10.0        | 0.8                              | MKT1820310405                                              |
|                         | 0.015        | 315                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820315405                                              |
|                         | 0.022        | 322                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820322405                                              |
|                         | 0.033        | 333                 |                 |                 | 4.0 x 9.0 x 13.0                               | 10.0        |                                  | MKT1820333405                                              |
|                         | 0.047        | 347                 |                 |                 | 4.5 x 9.5 x 13.0                               | 10.0        |                                  | MKT1820347405                                              |
|                         | 0.068        | 368                 |                 |                 | 5.5 x 10.5 x 13.0                              | 10.0        |                                  | MKT1820368405                                              |
|                         | 0.10         | 410                 |                 |                 | 6.5 x 11.5 x 13.0                              | 10.0        |                                  | MKT1820410405                                              |
|                         | 0.15         | 415                 |                 |                 | 9.0 x 15.5 x 13.0                              | 10.0        |                                  | MKT1820415405M                                             |
|                         | 0.15         | 415                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820415405                                              |
|                         | 0.22         | 422                 |                 |                 | 9.0 x 15.5 x 13.0                              | 10.0        |                                  | MKT1820422405M                                             |
|                         | 0.22         | 422                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820422405                                              |
|                         | 0.33         | 433                 |                 |                 | 7.5 x 13.5 x 18.0                              | 15.0        |                                  | MKT1820433405                                              |
|                         | 0.47         | 447                 |                 |                 | 8.5 x 17.5 x 18.0                              | 15.0        |                                  | MKT1820447405                                              |
|                         | 0.68         | 468                 |                 |                 | 8.5 x 16.5 x 26.5                              | 22.5        |                                  | MKT1820468405                                              |
|                         | 1.0          | 510                 |                 |                 | 10.5 x 18.5 x 26.5                             | 22.5        |                                  | MKT1820510405                                              |
|                         | 1.5          | 515                 |                 |                 | 11.0 x 21.0 x 26.5                             | 22.5        |                                  | MKT1820515405M                                             |
|                         | 1.5          | 515                 |                 |                 | 11.0 x 21.0 x 31.0                             | 27.5        |                                  | MKT1820515405                                              |
|                         | 2.2          | 522                 |                 |                 | 13.5 x 23.5 x 31.5                             | 27.5        |                                  | MKT1820522405                                              |
|                         | 3.3          | 533                 |                 |                 | 15 x 24.5 x 31.5                               | 27.5        |                                  | MKT1820533405                                              |
|                         | 4.7          | 547                 |                 |                 | 18.0 x 28.0 x 31.5                             | 27.5        |                                  | MKT1820547405                                              |

**Notes**

(1) For tolerances see chapter "Space Requirements for Printed-Circuit Board Applications and Dimension Tolerances"

(2) Please replace "5" by: "4" for 5 % tolerance or "6" for 20 % tolerance



| ELECTRICAL DATA         |              |                     |                 |                 |                                                |             |                                  |                                                            |
|-------------------------|--------------|---------------------|-----------------|-----------------|------------------------------------------------|-------------|----------------------------------|------------------------------------------------------------|
| U <sub>RDC</sub><br>(V) | CAP.<br>(μF) | CAPACITANCE<br>CODE | VOLTAGE<br>CODE | V <sub>AC</sub> | DIMENSIONS<br>w x h x l<br>(mm) <sup>(1)</sup> | PCM<br>(mm) | d <sub>t</sub> ± 0.08 mm<br>(mm) | ORDERING CODE FOR 10 %<br>TOL./BULK PACKING <sup>(2)</sup> |
| 630                     | 0.0010       | 210                 | 63              | 220             | 3.5 x 8.0 x 13.0                               | 10.0        | 0.80                             | MKT1820210635                                              |
|                         | 0.0015       | 215                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820215635                                              |
|                         | 0.0022       | 222                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820222635                                              |
|                         | 0.0033       | 233                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820233635                                              |
|                         | 0.0047       | 247                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820247635                                              |
|                         | 0.0068       | 268                 |                 |                 | 3.5 x 8.0 x 13.0                               | 10.0        |                                  | MKT1820268635                                              |
|                         | 0.010        | 310                 |                 |                 | 4.0 x 9.0 x 13.0                               | 10.0        |                                  | MKT1820310635                                              |
|                         | 0.015        | 315                 |                 |                 | 4.5 x 9.5 x 13.0                               | 10.0        |                                  | MKT1820315635                                              |
|                         | 0.022        | 322                 |                 |                 | 5.5 x 10.5 x 13.0                              | 10.0        |                                  | MKT1820322635                                              |
|                         | 0.033        | 333                 |                 |                 | 6.5 x 11.5 x 13.0                              | 10.0        |                                  | MKT1820333635M                                             |
|                         | 0.033        | 333                 |                 |                 | 5.5 x 10.5 x 18.0                              | 15.0        |                                  | MKT1820333635                                              |
|                         | 0.047        | 347                 |                 |                 | 6.5 x 11.5 x 13.0                              | 10.0        |                                  | MKT1820347635M                                             |
|                         | 0.047        | 347                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820347635                                              |
|                         | 0.068        | 368                 |                 |                 | 7.5 x 13.5 x 18.0                              | 15.0        |                                  | MKT1820368635                                              |
|                         | 0.10         | 410                 |                 |                 | 7.5 x 13.5 x 18.0                              | 15.0        |                                  | MKT1820410635M                                             |
|                         | 0.10         | 410                 |                 |                 | 6.5 x 14.5 x 26.5                              | 22.5        |                                  | MKT1820410635                                              |
|                         | 0.15         | 415                 |                 |                 | 7.5 x 15.5 x 26.5                              | 22.5        |                                  | MKT1820415635                                              |
|                         | 0.22         | 422                 |                 |                 | 8.5 x 16.5 x 26.5                              | 22.5        |                                  | MKT1820422635                                              |
|                         | 0.33         | 433                 |                 |                 | 11.0 x 21.0 x 31.0                             | 27.5        |                                  | MKT1820433635                                              |
|                         | 0.47         | 447                 |                 |                 | 11.0 x 21.0 x 31.0                             | 27.5        |                                  | MKT1820447635                                              |
|                         | 0.68         | 468                 |                 |                 | 13.5 x 23.5 x 31.5                             | 27.5        |                                  | MKT1820468635                                              |
|                         | 1.0          | 510                 |                 |                 | 15.0 x 24.5 x 31.5                             | 27.5        |                                  | MKT1820510635                                              |
|                         | 1.5          | 515                 |                 |                 | 18.0 x 28.0 x 31.5                             | 27.5        |                                  | MKT1820515635                                              |
| 1000                    | 0.0010       | 210                 | 10              | 220             | 4.0 x 9.0 x 13.0                               | 10.0        | 0.80                             | MKT1820210105                                              |
|                         | 0.0015       | 215                 |                 |                 | 4.0 x 9.0 x 13.0                               | 10.0        |                                  | MKT1820215105                                              |
|                         | 0.0022       | 222                 |                 |                 | 4.0 x 9.0 x 13.0                               | 10.0        |                                  | MKT1820222105                                              |
|                         | 0.0033       | 233                 |                 |                 | 4.0 x 9.0 x 13.0                               | 10.0        |                                  | MKT1820233105                                              |
|                         | 0.0047       | 247                 |                 |                 | 5.5 x 10.5 x 13.0                              | 10.0        |                                  | MKT1820247105                                              |
|                         | 0.0068       | 268                 |                 |                 | 6.5 x 11.5 x 13.0                              | 10.0        |                                  | MKT1820268105                                              |
|                         | 0.010        | 310                 |                 |                 | 5.5 x 10.5 x 18.0                              | 15.0        |                                  | MKT1820310105                                              |
|                         | 0.015        | 315                 |                 |                 | 6.5 x 12.5 x 18.0                              | 15.0        |                                  | MKT1820315105                                              |
|                         | 0.022        | 322                 |                 |                 | 7.5 x 13.5 x 18.0                              | 15.0        |                                  | MKT1820322105                                              |
|                         | 0.033        | 333                 |                 |                 | 8.5 x 14.5 x 18.0                              | 15.0        |                                  | MKT1820333105M                                             |
|                         | 0.033        | 333                 |                 |                 | 6.5 x 14.5 x 26.5                              | 22.5        |                                  | MKT1820333105                                              |
|                         | 0.047        | 347                 |                 |                 | 7.5 x 15.5 x 26.5                              | 22.5        |                                  | MKT1820347105                                              |
|                         | 0.068        | 368                 |                 |                 | 8.5 x 16.5 x 26.5                              | 22.5        |                                  | MKT1820368105                                              |
|                         | 0.10         | 410                 |                 |                 | 10.5 x 18.5 x 26.5                             | 22.5        |                                  | MKT1820410105                                              |
|                         | 0.15         | 415                 |                 |                 | 11.0 x 21.0 x 31.0                             | 27.5        |                                  | MKT1820415105                                              |
|                         | 0.22         | 422                 |                 |                 | 13.5 x 23.5 x 31.5                             | 27.5        |                                  | MKT1820422105                                              |
|                         | 0.33         | 433                 |                 |                 | 16.5 x 29.5 x 31.5                             | 27.5        |                                  | MKT1820433105                                              |
|                         | 0.47         | 447                 |                 |                 | 20.0 x 35.0 x 31.5                             | 27.5        |                                  | MKT1820447105                                              |

**Notes**

(1) For tolerances see chapter "Space Requirements for Printed-Circuit Board Applications and Dimension Tolerances"

(2) Please replace "5" by: "4" for 5 % tolerance or "6" for 20 % tolerance

| RECOMMENDED PACKAGING |                      |                    |                                 |                           |             |             |                       |                       |
|-----------------------|----------------------|--------------------|---------------------------------|---------------------------|-------------|-------------|-----------------------|-----------------------|
| PACKAGING<br>CODE     | TYPE OF<br>PACKAGING | HEIGHT (H)<br>(mm) | REEL DIAMETER/<br>BOX SIZE (mm) | ORDERING CODE<br>EXAMPLES | PITCH<br>10 | PITCH<br>15 | PITCH<br>22.5 TO 27.5 | PITCH<br>37.5 TO 52.5 |
| G                     | Ammo                 | 18.5               | 55 x 210 x 340                  | MKT1820410405G            | x           | x           | -                     | -                     |
| W                     | Reel                 | 18.5               | 350                             | MKT1820410405W            | x           | x           | -                     | -                     |
| V                     | Reel                 | 18.5               | 500                             | MKT1820422635V            | -           | x           | x                     | -                     |
| G                     | Ammo                 | 18.5               | 60 x 360 x 510                  | MKT1820422635G            | -           | -           | x                     | -                     |
| -                     | Bulk                 | -                  | -                               | MKT1820515405             | x           | x           | x                     | x                     |

**EXAMPLE OF ORDERING CODE**

| TYPE    | CAPACITANCE CODE | VOLTAGE CODE | TOLERANCE CODE <sup>(1)</sup> | PACKAGING CODE |
|---------|------------------|--------------|-------------------------------|----------------|
| MKT1820 | 410              | 06           | 5                             | G              |

**MOUNTING**
**Normal Use**

The capacitors are designed for mounting on printed-circuit boards. The capacitors packed in bandoleers are designed for mounting on printed-circuit boards by means of automatic insertion machines.

For detailed tape specifications refer to packaging information [www.vishay.com/docs?28139](http://www.vishay.com/docs?28139)

**Specific Method of Mounting to Withstand Vibration and Shock**

In order to withstand vibration and shock tests, it must be ensured that the stand-off pips are in good contact with the printed-circuit board.


- For pitches  $\leq 15$  mm the capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped

**SPACE REQUIREMENTS FOR PRINTED-CIRCUIT BOARD APPLICATIONS AND DIMENSION TOLERANCES**

For the maximum product dimensions and maximum space requirements for length ( $l_{max.}$ ), width ( $w_{max.}$ ), and height ( $h_{max.}$ ) following tolerances must be taken in account in the envelopment of the components as shown in the drawings below:

- For products with pitch  $\leq 15$  mm,  $\Delta w = \Delta l = 0.3$  mm, and  $\Delta h = 0.1$  mm
- For products with  $15 \text{ mm} < \text{pitch} \leq 27.5$  mm,  $\Delta w = \Delta l = 0.5$  mm, and  $\Delta h = 0.1$  mm
- For products with pitch = 37.5 mm,  $\Delta w = \Delta l = 0.7$  mm, and  $\Delta h = 0.5$  mm
- For products with pitch = 52.5 mm,  $\Delta w = \Delta l = 1.0$  mm, and  $\Delta h = 0.5$  mm

Eccentricity defined as in drawing. The maximum eccentricity is smaller than or equal to the lead diameter of the product concerned.



For the minimum product dimensions for length ( $l_{min.}$ ), width ( $w_{min.}$ ), and height ( $h_{min.}$ ) following tolerances of the components are valid:

$l_{min.} = l - \Delta l$ ,  $w_{min.} = w - \Delta w$ , and  $h_{min.} = h - \Delta h$  following

- For products with pitch  $\leq 10$  mm,  $\Delta l = 0.3$  mm, and  $\Delta w = \Delta h = 0.3$  mm
- For products with pitch = 15 mm,  $\Delta l = 0.5$  mm, and  $\Delta w = \Delta h = 0.5$  mm
- For products with  $15 \text{ mm} < \text{pitch} \leq 27.5$  mm,  $\Delta l = 1.0$  mm, and  $\Delta w = \Delta h = 0.5$  mm
- For products with pitch = 37.5 mm,  $\Delta l = 1.0$  mm, and  $\Delta w = \Delta h = 1.0$  mm
- For products with pitch = 52.5 mm,  $\Delta l = 1.5$  mm, and  $\Delta w = \Delta h = 1.0$  mm

**SOLDERING CONDITIONS**

For general soldering conditions and wave soldering profile, we refer to the application note:

“Soldering Guidelines for Film Capacitors”: [www.vishay.com/doc?28171](http://www.vishay.com/doc?28171)

**Storage Temperature**

$T_{stg} = -25$  °C to  $+35$  °C with RH maximum 75 % without condensation

**Ratings and Characteristics Reference Conditions**

Unless otherwise specified, all electrical values apply to an ambient free temperature of  $23$  °C  $\pm 1$  °C, an atmospheric pressure of 86 kPa to 106 kPa and a relative humidity of  $50\% \pm 2\%$ .







For reference testing, a conditioning period shall be applied over  $96 \text{ h} \pm 4 \text{ h}$  by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.





## CHARACTERISTICS


PERMISSIBLE AC VOLTAGE VS. FREQUENCY AT  $T_{amb} \leq 85^\circ\text{C}$






## CHARACTERISTICS


PERMISSIBLE AC VOLTAGE VS. FREQUENCY AT  $T_{amb} \leq 85^\circ\text{C}$




## CHARACTERISTICS




Nominal voltage (AC and DC) as a function of temperature




Capacitance as a function of temperature (typical curve)




Capacitance as a function of frequency (typical curve)




Dissipation factor as a function of temperature (typical curve)



Insulation resistance as a function of temperature  
(typical curve)



Dissipation Factor vs. Frequency  $\tan \delta = f(f)$   
Dissipation factor as a function of frequency  
(typical curve)



Maximum allowed component temperature rise (ΔT)  
as function of ambient temperature (T<sub>amb</sub>)

| <b>HEAT CONDUCTIVITY (G) AS A FUNCTION OF CAPACITOR BODY THICKNESS IN mW/°C</b> |                                  |                      |                      |                      |                      |                      |
|---------------------------------------------------------------------------------|----------------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| <b>W<sub>max.</sub><br/>(mm)</b>                                                | <b>HEAT CONDUCTIVITY (mW/°C)</b> |                      |                      |                      |                      |                      |
|                                                                                 | <b>PITCH 10.0 mm</b>             | <b>PITCH 15.0 mm</b> | <b>PITCH 22.5 mm</b> | <b>PITCH 27.5 mm</b> | <b>PITCH 37.5 mm</b> | <b>PITCH 52.5 mm</b> |
| 3.5                                                                             | 5.0                              | -                    | -                    | -                    | -                    | -                    |
| 4.0                                                                             | 6.0                              | -                    | -                    | -                    | -                    | -                    |
| 4.5                                                                             | 7.0                              | -                    | -                    | -                    | -                    | -                    |
| 5.5                                                                             | 8.0                              | 10.0                 | -                    | -                    | -                    | -                    |
| 6.5                                                                             | 10.0                             | 13.0                 | 20.0                 | -                    | -                    | -                    |
| 7.5                                                                             | -                                | 15.0                 | 22.0                 | -                    | -                    | -                    |
| 8.5                                                                             | -                                | 16.0                 | 24.0                 | -                    | -                    | -                    |
| 9.0                                                                             | -                                | -                    | -                    | 32.0                 | -                    | -                    |
| 10.5                                                                            | -                                | -                    | 30.0                 | -                    | -                    | -                    |
| 11.0                                                                            | -                                | -                    | -                    | 38.0                 | -                    | -                    |
| 11.5                                                                            | -                                | -                    | -                    | 38.0                 | -                    | -                    |
| 12.5                                                                            | -                                | -                    | 34.0                 | -                    | -                    | -                    |
| 13.0                                                                            | -                                | -                    | -                    | 45.0                 | -                    | -                    |
| 13.5                                                                            | -                                | -                    | -                    | 45.0                 | -                    | -                    |
| 15.0                                                                            | -                                | -                    | -                    | 50.0                 | -                    | -                    |
| 16.5                                                                            | -                                | -                    | -                    | 58.0                 | -                    | -                    |
| 18.0                                                                            | -                                | -                    | -                    | 60.0                 | -                    | -                    |
| 18.5                                                                            | -                                | -                    | -                    | -                    | 90.0                 | -                    |
| 20.0                                                                            | -                                | -                    | -                    | 73.0                 | -                    | -                    |
| 21.0                                                                            | -                                | -                    | -                    | 70.0                 | -                    | -                    |
| 21.5                                                                            | -                                | -                    | -                    | -                    | 102.0                | -                    |
| 24.0                                                                            | -                                | -                    | -                    | -                    | 118.0                | -                    |
| 25.0                                                                            | -                                | -                    | -                    | -                    | -                    | 155.0                |
| 30.0                                                                            | -                                | -                    | -                    | -                    | 135.0                | 170.0                |
| 35.0                                                                            | -                                | -                    | -                    | -                    | -                    | 200.0                |

## POWER DISSIPATION AND MAXIMUM COMPONENT TEMPERATURE RISE


The power dissipation must be limited in order not to exceed the maximum allowed component temperature rise as a function of the free air ambient temperature.

The component temperature rise ( $\Delta T$ ) can be measured or calculated by  $\Delta T = P/G$ :

- $\Delta T$  = component temperature rise (°C) with a maximum of 15 °C
- P = power dissipation of the component (mW)
- G = heat conductivity of the component (mW/°C)

## MEASURING THE COMPONENT TEMPERATURE

A thermocouple must be attached to the capacitor body as in:



The temperature is measured in unloaded ( $T_{amb}$ ) and maximum loaded condition ( $T_C$ ).

The temperature rise is given by  $\Delta T = T_C - T_{amb}$ .

To avoid thermal radiation or convection, the capacitor must be tested in a closed area from air circulation.

## APPLICATION NOTE AND LIMITING CONDITIONS

These capacitors are not suitable for mains applications as across-the-line capacitors without additional protection, as described hereunder. These mains applications are strictly regulated in safety standards and therefore electromagnetic interference suppression capacitors conforming the standards must be used.

To select the capacitor for a certain application, the following conditions must be checked:

1. The peak voltage ( $U_P$ ) shall not be greater than the rated DC voltage ( $U_{RDC}$ )
2. The peak-to-peak voltage ( $U_{P-P}$ ) shall not be greater than the maximum ( $U_{P-P}$ ) to avoid the ionization inception level
3. The voltage peak slope ( $dU/dt$ ) shall not exceed the rated voltage pulse slope in an RC-circuit at rated voltage and without ringing. If the pulse voltage is lower than the rated DC voltage, the rated voltage pulse slope may be multiplied by  $U_{RDC}$  and divided by the applied voltage.

For all other pulses following equation must be fulfilled:

$$2 \times \int_0^T \left( \frac{dU}{dt} \right)^2 \times dt < U_{NDC} \times \left( \frac{dU}{dt} \right)_{rated}$$

T is the pulse duration.

4. The maximum component surface temperature rise must be lower than the limits (see graph "Max. allowed component temperature rise").
5. Since in circuits used at voltages over 280 V peak-to-peak the risk for an intrinsically active flammability after a capacitor breakdown (short circuit) increases, it is recommended that the power to the component is limited to 100 times the values mentioned in the table: "Heat conductivity"
6. When using these capacitors as across-the-line capacitor in the input filter for mains applications or as series connected with an impedance to the mains the applicant must guarantee that the following conditions are fulfilled in any case (spikes and surge voltages from the mains included).
7. For capacitors connected in parallel, normally the proof voltage and possibly the rated voltage must be reduced. For information depending of the capacitance value and the number of parallel connections contact [dc-film@vishay.com](mailto:dc-film@vishay.com).

| <b>VOLTAGE CONDITIONS FOR 6 ABOVE</b>        |                                                   |                                                                          |                                                                           |
|----------------------------------------------|---------------------------------------------------|--------------------------------------------------------------------------|---------------------------------------------------------------------------|
| <b>ALLOWED VOLTAGES</b>                      | <b><math>T_{amb} \leq 85^\circ\text{C}</math></b> | <b><math>85^\circ\text{C} &lt; T_{amb} \leq 100^\circ\text{C}</math></b> | <b><math>100^\circ\text{C} &lt; T_{amb} \leq 125^\circ\text{C}</math></b> |
| Maximum continuous RMS voltage               | $U_{RAC}$                                         | $0.8 \times U_{RAC}$                                                     | $0.5 \times U_{RAC}$                                                      |
| Maximum temperature RMS-overvoltage (< 24 h) | $1.25 \times U_{RAC}$                             | $U_{RAC}$                                                                | $0.6 \times U_{RAC}$                                                      |
| Maximum peak voltage ( $V_{O-P}$ ) (< 2 s)   | $1.6 \times U_{RDC}$                              | $1.3 \times U_{RDC}$                                                     | $0.5 \times U_{RDC}$                                                      |

**INSPECTION REQUIREMENTS****General Notes**

Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, Publication IEC 60384-2 and Specific Reference Data”.

| <b>GROUP C INSPECTION REQUIREMENTS</b>              |                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SUB-CLAUSE NUMBER AND TEST</b>                   | <b>CONDITIONS</b>                                                                                                                                                                                                            | <b>PERFORMANCE REQUIREMENTS</b>                                                                                                                                                                                                                                                                                    |
| <b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b> |                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                    |
| 4.1 Dimensions (detail)                             |                                                                                                                                                                                                                              | As specified in chapter “General Data” of this specification                                                                                                                                                                                                                                                       |
| 4.3.1 Initial measurements                          | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz                                                |                                                                                                                                                                                                                                                                                                                    |
| 4.3 Robustness of terminations                      | Tensile and bending                                                                                                                                                                                                          | No visible damage                                                                                                                                                                                                                                                                                                  |
| 4.4 Resistance to soldering heat                    | Method: 1A<br>Solder bath: $280 \text{ }^{\circ}\text{C} \pm 5 \text{ }^{\circ}\text{C}$<br>Duration: 10 s                                                                                                                   |                                                                                                                                                                                                                                                                                                                    |
| 4.14 Component solvent resistance                   | Isopropylalcohol at room temperature<br>Method: 2<br>Immersion time: 5 min $\pm$ 0.5 min<br>Recovery time: min. 1 h, max. 2 h                                                                                                |                                                                                                                                                                                                                                                                                                                    |
| 4.4.2 Final measurements                            | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle                                                                                                                                                           | No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 2 \%$ of the value measured initially<br><br>Increase of $\tan \delta$ :<br>$\leq 0.003$ for $C \leq 1 \mu\text{F}$ or<br>$\leq 0.002$ for $C > 1 \mu\text{F}$<br>$\leq 0.004$ for $C \geq 100 \mu\text{F}$<br>Compared to values measured in 4.3.1 |
| <b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b> |                                                                                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                    |
| 4.6.1 Initial measurements                          | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz                                                |                                                                                                                                                                                                                                                                                                                    |
| 4.6 Rapid change of temperature                     | $\theta A = -55 \text{ }^{\circ}\text{C}$<br>$\theta B = +125 \text{ }^{\circ}\text{C}$<br>5 cycles<br>Duration $t = 30 \text{ min}$<br>Visual examination                                                                   | No visible damage<br>Legible marking                                                                                                                                                                                                                                                                               |
| 4.7 Vibration                                       | Mounting:<br>see section “Mounting” of this specification<br>Procedure B4<br>Frequency range: 10 Hz to 55 Hz<br>Amplitude: 0.75 mm or<br>Acceleration $98 \text{ m/s}^2$<br>(whichever is less severe)<br>Total duration 6 h |                                                                                                                                                                                                                                                                                                                    |
| 4.7.2 Final inspection                              | Visual examination                                                                                                                                                                                                           | No visible damage                                                                                                                                                                                                                                                                                                  |
| 4.9 Shock                                           | Mounting:<br>see section “Mounting” for more information<br>Pulse shape: half sine<br>Acceleration: $490 \text{ m/s}^2$<br>Duration of pulse: 11 ms                                                                          |                                                                                                                                                                                                                                                                                                                    |



| GROUP C INSPECTION REQUIREMENTS                                            |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SUB-CLAUSE NUMBER AND TEST                                                 | CONDITIONS                                                                                                                                                                                                                                                                                                                      | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>SUB-GROUP C1B PART OF SAMPLE OF SUB-GROUP C1</b>                        |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.9.3 Final measurements                                                   | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz<br><br>Insulation resistance                                                                                         | No visible damage<br><br>$ \Delta C/C  \leq 5\%$ of the value measured in 4.6.1<br><br>Increase of $\tan \delta$ :<br>$\leq 0.003$ for $C \leq 1 \mu\text{F}$ or<br>$\leq 0.002$ for $C > 1 \mu\text{F}$<br>$\leq 0.004$ for $C \geq 100 \mu\text{F}$<br>Compared to values measured in 4.6.1<br><br>As specified in section "Insulation Resistance" of this specification                                                                                          |
| <b>SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B</b> |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.10 Climatic sequence                                                     |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.10.2 Dry heat                                                            | Temperature: +125 °C<br>Duration: 16 h                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.10.3 Damp heat cyclic<br>Test Db, first cycle                            |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.10.4 Cold                                                                | Temperature: -55 °C<br>Duration: 2 h                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.10.6 Damp heat cyclic<br>Test Db, remaining cycles                       |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.10.6.2 Final measurements                                                | Voltage proof = $U_{RDC}$ for 1 min within 15 min after removal from testchamber<br><br>Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz<br><br>Insulation resistance | No breakdown or flashover<br><br>No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 5\%$ of the value measured in 4.4.2 or 4.9.3<br><br>Increase of $\tan \delta$ :<br>$\leq 0.005$ for $C \leq 1 \mu\text{F}$ or<br>$\leq 0.003$ for $C > 1 \mu\text{F}$<br>$\leq 0.004$ for $C \geq 100 \mu\text{F}$<br>Compared to values measured in 4.3.1 or 4.6.1<br><br>$\geq 50\%$ of values specified in section "Insulation Resistance" of this specification |
| <b>SUB-GROUP C2</b>                                                        |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.11 Damp heat steady state                                                | 56 days; 40 °C; 90 % to 95 % RH                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.11.1 Initial measurements                                                | Capacitance<br><br>Tangent of loss angle<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| 4.11.3 Final measurements                                                  | Voltage proof = $U_{RDC}$ for 1 min within 15 min after removal from testchamber<br><br>Visual examination                                                                                                                                                                                                                      | No breakdown or flashover<br><br>No visible damage<br>Legible marking                                                                                                                                                                                                                                                                                                                                                                                               |



| GROUP C INSPECTION REQUIREMENTS |                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SUB-CLAUSE NUMBER AND TEST      | CONDITIONS                                                                                                                                                                                                                              | PERFORMANCE REQUIREMENTS                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <b>SUB-GROUP C2</b>             |                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4.11.3 Final measurements       | Capacitance<br><br>Tangent of loss angle<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz<br><br>Insulation resistance                           | $ \Delta C/C  \leq 5 \%$ of the value measured in 4.11.1.<br><br>Increase of $\tan \delta$<br>$\leq 0.005$ for $C \leq 1 \mu\text{F}$ or<br>$\leq 0.003$ for $C > 1 \mu\text{F}$<br>$\leq 0.004$ for $C \geq 100 \mu\text{F}$<br>Compared to values measured in 4.11.1<br><br>$\geq 50 \%$ of values specified in section<br>"Insulation Resistance" of this specification                                                                         |
| <b>SUB-GROUP C3</b>             |                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4.12 Endurance                  | Duration: 2000 h<br>1.25 x $U_{\text{RDC}}$ at 85 °C<br>1.0 x $U_{\text{RDC}}$ at 100 °C<br>0.6 x $U_{\text{RDC}}$ at 125 °C<br>Duration: 200 h<br>0.3 x $U_{\text{RDC}}$ at 150 °C<br>(not applicable for pitch $\geq 37.5$ mm)        |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4.12.1 Initial measurements     | Capacitance<br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4.12.5 Final measurements       | Visual examination<br><br>Capacitance<br><br>Tangent of loss angle<br>For $C \leq 1 \mu\text{F}$ at 10 kHz<br>For $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>For $C \geq 100 \mu\text{F}$ at 100 Hz<br><br>Insulation resistance | No visible damage<br>Legible marking<br><br>$ \Delta C/C  \leq 5 \%$ compared to values measured<br>in 4.12.1<br><br>Increase of $\tan \delta$ :<br>$\leq 0.003$ for $C \leq 1 \mu\text{F}$ or<br>$\leq 0.002$ for $1 \mu\text{F} < C < 100 \mu\text{F}$<br>$\leq 0.004$ for $C \geq 100 \mu\text{F}$<br>Compared to values measured in 4.12.1<br><br>$\geq 50 \%$ of values specified in section<br>"Insulation Resistance" of this specification |
| <b>SUB-GROUP C4</b>             |                                                                                                                                                                                                                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4.13 Charge and discharge       | 10 000 cycles<br>Charged to $U_{\text{RDC}}$<br>Discharge resistance:<br>$R = \frac{U_R}{C \times K \times (dU/dt)_R}$ K = 5 for pitch $\leq 27.5$ mm<br>K = 1.5 for pitch 37.5 mm/52.5 mm                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4.13.1 Initial measurements     | Capacitance<br><br>Tangent of loss angle:<br>for $C \leq 1 \mu\text{F}$ at 10 kHz<br>for $1 \mu\text{F} < C < 100 \mu\text{F}$ at 1 kHz<br>for $C \geq 100 \mu\text{F}$ at 100 Hz                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| 4.13.3 Final measurements       | Capacitance<br><br>Tangent of loss angle:<br><br><br>Insulation resistance                                                                                                                                                              | $ \Delta C/C  \leq 3 \%$ compared to values measured<br>in 4.13.1<br><br>Increase of $\tan \delta$ :<br>$\leq 0.003$ for $C \leq 1 \mu\text{F}$ or<br>$\leq 0.002$ for $C > 1 \mu\text{F}$<br>$\leq 0.004$ for $C \geq 100 \mu\text{F}$<br>Compared to values measured in 4.13.1<br><br>$\geq 50 \%$ of values specified in section<br>"Insulation Resistance" of this specification                                                               |





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vishay:

[MKT1820568015](#) [MKT1820610064](#) [MKT1820610014](#) [MKT1820510255](#) [MKT1820682255](#) [MKT1820682015](#)  
[MKT1820747065](#) [MKT1820682165](#) [MKT1820715165](#) [MKT1820718015](#) [MKT1820722165](#) [MKT1820733015](#)  
[MKT1820722065](#) [MKT1820756065](#) [MKT1820712255](#) [MKT1820710065](#) [MKT1820727065M](#)