


Inductors

High Frequency, Surface Mount, Molded



FEATURES

- High self-resonant frequency values
- High Q values at higher frequencies
- Molded construction provides superior strength and moisture resistance
- Wirewound construction
- Tape and reel packaging for automatic handling, 3000/reel, EIA481
- Compatible with vapor phase and infrared reflow soldering
- 100 % Lead (Pb)-free and RoHS compliant


RoHS
COMPLIANT

STANDARD ELECTRICAL SPECIFICATIONS

IND. (nH)	TOL.	TEST FREQ. L & Q (MHz)	Q MIN.	Q TYPICAL			SELF- RESONANT FREQ. MIN. (MHz)	DCR ± 30 % (Ohms)	RATED DC CURRENT (mA)
				100 MHz	800 MHz	1.8 GHz			
10	± 10 %	100	10	22	65	110	3300	0.14	540
12	± 10 %	100	10	22	65	105	3300	0.18	535
15	± 10 %	100	12	23	70	100	3000	0.18	520
18	± 10 %	100	12	25	75	95	3000	0.22	480
22	± 10 %	100	15	25	75	80	2600	0.22	465
27	± 10 %	100	15	25	75	—	2500	0.26	455
33	± 5 %, ± 10 %	100	15	28	80	—	2050	0.30	395
39	± 5 %, ± 10 %	100	15	28	70	—	2000	0.31	390
47	± 5 %, ± 10 %	100	15	28	70	—	1650	0.35	385
56	± 5 %, ± 10 %	100	15	28	60	—	1550	0.39	360
68	± 5 %, ± 10 %	100	15	28	—	—	1450	0.44	340
82	± 5 %, ± 10 %	100	15	28	—	—	1100	0.48	330
100	± 5 %, ± 10 %	25.2	8	25	—	—	800	0.66	285
120	± 5 %, ± 10 %	25.2	8	24	—	—	600	0.76	275
150	± 5 %, ± 10 %	25.2	10	25	—	—	600	1.13	230
180	± 5 %, ± 10 %	25.2	10	25	—	—	600	1.24	195
220	± 5 %, ± 10 %	25.2	10	25	—	—	500	1.41	170
270	± 5 %, ± 10 %	25.2	10	25	—	—	300	1.50	165
330	± 5 %, ± 10 %	25.2	10	20	—	—	200	1.66	160
390	± 5 %, ± 10 %	25.2	10	20	—	—	150	1.82	150
470	± 5 %, ± 10 %	25.2	10	18	—	—	150	1.97	145
560	± 5 %, ± 10 %	25.2	10	15	—	—	100	2.07	140
680	± 5 %, ± 10 %	25.2	10	—	—	—	100	2.32	130
820	± 5 %, ± 10 %	25.2	10	—	—	—	80	2.60	125
1000	± 5 %, ± 10 %	7.96	8	—	—	—	80	2.98	120

NOTE: Tighter tolerance product may be substituted based on availability.

ELECTRICAL SPECIFICATIONS

Inductance Range: 3.9 nH to 1000 nH

Inductance Tolerance: ± 20 % for 3.9 nH to 8.2 nH

± 10 % for 6.8 nH to 1000 nH

± 5 % for 33 nH to 1000 nH


Temperature Range: - 40 °C to +105 °C (no load). - 40 °C to + 85 °C (at full rated current)

Core Material: Non-magnetic.


TEST EQUIPMENT

- Inductance and Q measured on HP4191A
- SRF measured on HP8753B

DIMENSIONS in inches [millimeters]



Recommended Pad Layout



DESCRIPTION

IMC-0805 MODEL	10 nH INDUCTANCE VALUE	± 1 0% INDUCTANCE TOLERANCE	ER PACKAGE CODE	e3 JEDEC LEAD FREE STANDARD
-------------------	------------------------------	-----------------------------------	-----------------------	-----------------------------------

GLOBAL PART NUMBER

I	M	C	0	8	0	5	E	R	1	0	N	K
PRODUCT FAMILY			SIZE				PACKAGE CODE		INDUCTANCE VALUE			TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.



Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

SMD Magnetics Packaging Methods

TAPE AND REEL in inches [millimeters]

Tape and Reel



MODEL	PACKAGE CODE			REEL SIZE	CARRIER TAPE WIDTH (W)	COMPONENT PITCH (P)	UNITS/ REEL	PACKAGE CODE			UNITS/ BULK
	PREVIOUS CODE	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE					PREVIOUS CODE	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD (Pb)-FREE	
IHLP-1616AB-01	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	4000	-	-	EB	100
IHLP-1616AB-11	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	4000	-	-	EB	100
IHLP-1616BZ-01	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	4000	-	-	EB	100
IHLP-1616BZ-11	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	4000	-	-	EB	100
IHLP-2525AH	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	2000	-	-	EB	100
IHLP-2525BD	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	2000	-	-	EB	100
IHLP-2525CZ	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	2000	-	-	EB	100
IHLP-2525EZ	-	-	ER	13	0.630 [16.0]	0.472 [12.0]	500	-	-	EB	100
IHLP-4040DZ	-	-	ER	13	0.945 [24.0]	0.630 [16.0]	500	-	-	EB	100
IHLP-5050CE	-	-	ER	13	0.945 [24.0]	0.630 [16.0]	500	-	-	EB	100
IHLP-5050EZ	-	-	ER	13	0.945 [24.0]	0.630 [16.0]	250	-	-	EB	100
IHLP-5050FD	-	-	ER	13	0.945 [24.0]	0.630 [16.0]	250	-	-	EB	100
IHLM-2525CZ	-	-	ER	13	0.630 [16.0]	0.315 [8.0]	2000	-	-	EB	100
IHSM-3825	RC2	RE	ER	13	0.945 [24.0]	0.472 [12.0]	750	P09	PJ	EB	100
IHSM-4825	RC2	RE	ER	13	0.945 [24.0]	0.472 [12.0]	750	P09	PJ	EB	100
IHSM-5832	RC3	RF	ER	13	1.26 [32.0]	0.472 [12.0]	500	P09	PJ	EB	100
IHSM-7832	RC4	RG	ER	13	1.73 [44.0]	0.472 [12.0]	500	P09	PJ	EB	100
IDC-2512	R96	NB	ER	13	0.630 [16.0]	0.315 [8.0]	2000	-	-	-	-
IDC-5020	R96	NB	ER	13	0.630 [16.0]	0.472 [12.0]	500	-	-	-	-
IDC-7328	R96	NB	ER	13	0.945 [24.0]	0.945 [24.0]	250	-	-	-	-
IDCS-2512	R96	NB	ER	13	0.630 [16.0]	0.315 [8.0]	2000	-	-	-	-
IDCS-5020	R96	NB	ER	13	0.630 [16.0]	0.472 [12.0]	500	-	-	-	-
IDCS-7328	R96	NB	ER	13	0.945 [24.0]	0.945 [24.0]	250	-	-	-	-
IDCP-1813	R96	NB	ER	13	0.472 [12.0]	0.315 [8.0]	2000	-	-	-	-
IDCP-2218	R96	NB	ER	13	0.472 [12.0]	0.315 [8.0]	1500	-	-	-	-
IDCP-3114	R96	NB	ER	13	0.630 [16.0]	0.472 [12.0]	1000	-	-	-	-
IDCP-3020	R96	NB	ER	13	0.630 [16.0]	0.472 [12.0]	1000	-	-	-	-
IDCP-3722	R96	NB	ER	13	0.945 [24.0]	0.472 [12.0]	800	-	-	-	-
IDCP-3916	R96	NB	ER	13	0.945 [24.0]	0.472 [12.0]	800	-	-	-	-
IFC-0603	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	5000	-	-	-	-
IFC-0805	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	5000	-	-	-	-
IFCB-0402	-	-	ER	7	0.315 [8.0]	0.079 [2.0]	10 000	-	-	-	-
IFCB-0603	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	5000	-	-	-	-
ILC-0402	-	-	ER	7	0.315 [8.0]	0.079 [2.0]	10 000	-	-	-	-
ILC-0603	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	4000	-	-	-	-
IMC-0402	-	-	ER	7	0.315 [8.0]	0.079 [2.0]	10 000	-	-	-	-
IMC-0402-01	-	-	ER	7	0.315 [8.0]	0.079 [2.0]	10 000	-	-	-	-
IMC-0603	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	3000	-	-	-	-
IMC-0603-01	-	-	ER	7	0.315 [8.0]	0.079 [2.0]	3000	-	-	-	-
IMC-0805	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	3000	-	-	-	-
IMC-0805-01	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	2000	-	-	-	-

TAPE AND REEL in inches [millimeters]											
MODEL	PACKAGE CODE			REEL SIZE	CARRIER TAPE WIDTH (W)	COMPONENT PITCH (P)	UNITS/ REEL	PACKAGE CODE			UNITS/ BULK
	PREVIOUS CODE	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD FREE					PREVIOUS CODE	GLOBAL CODE LEAD BEARING	GLOBAL CODE LEAD FREE	
IMC-1008	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	2000	-	-	-	-
IMC-1210	R98/RB3	SY/AN	ER/ET	7	0.315 [8.0]	0.157 [4.0]	2000	B13	BN	EB	500
	R99/RB4	SZ/R9	ES/EU	13	0.315 [8.0]	0.157 [4.0]	7500				
IMC-1210-100	R98/RB3	SY/AN	ER/ET	7	0.315 [8.0]	0.157 [4.0]	2000	B13	BN	EB	500
	R99/RB4	SZ/R9	ES/EU	13	0.315 [8.0]	0.157 [4.0]	7500				
IMC-1812	R73/R92	RV/RX	ER/ET	7	0.472 [12.0]	0.315 [8.0]	500	B13	BN	EB	500
	R13/R91	RQ/RW	ES/EU	13	0.472 [12.0]	0.315 [8.0]	2000				
IMCH-1812	-	-	ER	7	0.472 [12.0]	0.315 [8.0]	500	-	-	-	-
IMC-2220	-	-	ER	13	0.630 [16.0]	0.472 [12.0]	1000	-	-	-	-
ISC-1008	-	-	ER	13	0.472 [12.0]	0.157 [4.0]	750	-	-	-	-
ISC-1210	R98/RB3	SY/AN	ER/ET	7	0.315 [8.0]	0.157 [4.0]	2000	B13	BN	EB	500
	R99/RB4	SZ/R9	ES/EU	13	0.315 [8.0]	0.157 [4.0]	7500				
ISC-1812	R73/R92	RV/RX	ER/ET	7	0.472 [12.0]	0.315 [8.0]	500	B13	BN	EB	500
	R13/R91	RQ/RW	ES/EU	13	0.472 [12.0]	0.315 [8.0]	2000				
ICM-0805	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	2000	-	-	-	-
ICM-1206	-	-	ER	7	0.315 [8.0]	0.157 [4.0]	2000	-	-	-	-
ILSB-0603	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	4000	-	-	-	-
ILSB-0805 (0.047 - 2.2 μ H)	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	4000	-	-	-	-
ILSB-0805 (2.7 - 33 μ H)	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	3000	-	-	-	-
ILSB-1206	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	3000	-	-	-	-
ILBB-0402	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	10 000	-	-	-	-
ILBB-0603	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	4000	-	-	-	-
ILBB-0805	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	4000	-	-	-	-
ILB-1206	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	3000	-	-	-	-
	RT4	ND	ES	13	0.315 [8.0]	0.157 [4.0]	10 000				
ILBB-1210	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	2000	-	-	-	-
ILBB-1806	RC8	RK	ER	7	0.472 [12.0]	0.157 [4.0]	2000	-	-	-	-
ILBB-1812	RC8	RK	ER	7	0.472 [12.0]	0.157 [4.0]	1000	-	-	-	-
ILHB-0603	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	4000	-	-	-	-
ILHB-0805	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	4000	-	-	-	-
ILHB-1206	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	3000	-	-	-	-
ILHB-1806	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	2000	-	-	-	-
ILHB-1812	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	1000	-	-	-	-
ILAS-1206	RC8	RK	ER	7	0.315 [8.0]	0.157 [4.0]	3000	-	-	-	-
LPE-3325	R94	RY	ER	13	0.945 [24.0]	0.472 [12.0]	1000	S51	SM	EB	10
LPE-4841	R94	RY	ER	13	0.945 [24.0]	0.630 [16.0]	600	S51	SM	EB	10
LPE-5047	R94	RY	ER	13	0.945 [24.0]	0.630 [16.0]	600	S51	SM	EB	10
LPE-6562	R94	RY	ER	13	1.26 [32.0]	0.787 [20.0]	300	S51	SM	EB	10
LPE-6855	R94	RY	ER	13	1.26 [32.0]	0.787 [20.0]	450	S51	SM	EB	10
LPE-3325-CST	-	-	ER	13	0.945 [24.0]	0.472 [12.0]	1000	-	-	EB	10
LPT-3535	RC5	RH	ER	13	0.945 [24.0]	0.630 [16.0]	600	S51	SM	EB	10
LPT-4545	RC5	RH	ER	13	0.945 [24.0]	0.630 [16.0]	600	S51	SM	EB	10

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Vishay:](#)

[IMC0805RKR22J](#) [IMC0805RK5N6K](#) [IMC0805RK100K](#) [IMC0805BN180K](#) [IMC0805RK47NJ](#) [IMC0805RKR47J](#)
[IMC0805RK6N8K](#) [IMC0805RKR10J](#) [IMC0805RKR33J](#) [IMC0805 820 5%TR](#)