SAMZO | REAC/ROHS

REV	ECN NO	DESRIPTION	DESIGN	APPROVAL	DATE
A1	NEW	Replace frame			2020.06.12







Note
Materials
1.1 Plastic Core: LCP UL94 V - O
1.2 Terminals: C2680, with a thickness of ; nickel - based and gold - plated
1.3 Housing: Stainless Steel 201 - H with nickel - plated surface
Electrical Characteristics
2.1 Contact Area: The contact resistance is a maximum of 40mΩ, with an allowable change of 10mΩ. Test conditions: Measured at 20mV and 100mA.
2.2 Contact Current: 3A for the VBUS pin; 1.25A for the GND pin; 0.25A for other pins.
2.3 Rated Voltage: 5V.
2.4 Withstand Voltage: 100VAC.
2.5 Insulation Resistance: At least 100 MΩ.
Mechanical Properties
3.1 Insertion Force: 0.5 - 2.0 Kg
3.2 Withdrawal Force: 0.6 - 2.04 Kg
3.3 Insertion and Withdrawal Cycles: 5000 Cycles.
Operating Environment: - 20 to + 85 .







NO	PART	Q'TY	Material
1	SHELL	1	ZINC ALLOY,NI30u"Min PLATED
2	CONTACT	6	C2680,TIN80u"/Au1u"/NI30u" PLATED
3	IMD HOUSING	1	LCP UL94 V-0 BLACK
4	CAP	1	LCP UL94 V-0 BLACK
5	WATERPROOF RING	1	SILICONE UL94 V-0 BLACK

UKAKAT*BA
Ⓐ Ⓑ Ⓒ Ⓓ Ⓔ Ⓕ Ⓖ Ⓗ

A.SERISE：UK-TYPE C
B.SIZE：A-2pin
C.MOUNTING：K-WIRE-SOLDERING TYPE
D.LOOKS：A-L8.6
E.STYIE：T:GENERAL
F.MATERIAL：A-SUS201/C-SUS304
G.LIFETIME:B:5000 CYCLES
H.CODE：A-REGULAR

			GENERAL TOLERANCE	
			≥0~2<	±0.15
DESIGN	WANGGUIFA	2020.06.12	≥2~5<	±0.25
CHECKED	ZHENGUILAN	2020.06.12	≥0~2<	±0.15
APPROVED	LILIANJIANG	2020.06.14	≥5	±0.35

FIRST VIEW



SCALE 1:1 UNIT mm

SAMZO COMPONENTS
Electronic switch and connector manufacturer

The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts.
WWW.KKK-JP.COM

TITLE:：
TYPE-C 2Pin 8.6MM 焊线式
DWG NO：UKAK-P0000
PART NO：UKAK023500
MODEL NO：UKAKAT-*-BA
NAME：
TYPE-C CONN