

WiFi 2.4 GHz injector 7501.17.0011

Diplexer / Duplexer

Description

This diplexer links W-LAN designed to 802.11(b/g) with a coaxial distributed in-building cellular network or DAS working in the range from 80 to 2170 MHz. This gives W-LAN the benefit of the same controlled coverage as the DAS, eliminating many W-LAN uncertainties. To minimize the effects of the Injector to the DAS the inputs are well isolated and have minimal insertion loss.

The W-LAN Injector has been designed using passive, proprietary techniques to ensure minimal loss and high reliability. Corner holes are provided for simple mounting to a surface or cable tray.

This model has been designed and tested to meet the European Rail Standards:

EN50121

EN50155: 2001, EN61373: 1999

EN60068-2-1: 1995

EN60068-2-2: 1994

EN60068-2-30: 2000



Technical Data

Electrical Data

	Band 1	Band 2
Frequency	0.08 - 2.17 GHz	2.4 - 2.5 GHz
Return loss	14 dB	14 dB
Insertion loss	0.3 dB	0.6 dB
Insertion loss ripple	0.1 dB	0.1 dB
Band 1		50
Max. composite power	150 W	8 W
Peak envelope power	3000 W	
Intermodulation distortion	-140 dBc	-140 dBc
@ 2 x carrier power	43 dBm	43 dBm
Port Designation	J1	J2
Connector Type	N	N
Gender	jack (female)	jack (female)
Char. impedance	50 Ω all ports	

Common Port

Port designation	J3
Connector	N, jack (female)

Typical return loss for J1 and J2 in the range from 0 to 70°C: 17 dB

Typical PIM level < -150 dBc @ 2 x 43 dBm carrier power.

Mechanical Data

Dimensions	32.26 x 122.22 x 179.71 mm (Height x Width x Depth)
Weight	0.91 kg

Environmental Data

Environmental conditions	indoor/outdoor
Operation temperature	-40 °C to 85 °C
Storage temperature	-40 °C to 85 °C

WiFi 2.4 GHz injector 7501.17.0011

Transport temperature	-40 °C to 85 °C
IP rating	IP67
RoHS 2011/65/EC	compliant

Material Data

Housing Material	Aluminium , , A.00 , 0 ,
Surface treatment	Passivated

Related Documents

Mounting instruction	
Painting instruction	
Security instruction	
Outline drawing	DOU-00287022
3D-model (Step)	DOC-0000403115

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

7501.17.0011