

Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous to
---------------	--

Surge Protection and Filtering

Surge energy rating	600 Joules
Dataline protection	RJ-11 Modem/Fax protection,RJ45 10/100 Base-T Ethernet protection,Co-ax Cable protection

Physical

Maximum Height	372.00 mm
Maximum Width	225.00 mm
Maximum depth	105.00 mm
Net Weight	7.42 KG
Shipping Weight	8.41 KG
Shipping Height	470.00 mm
Shipping Width	305.00 mm
Shipping Depth	165.00 mm
Master Carton Units	2.00
Master Carton Weight	37.05 lbs.
Color	Beige
SCC Codes	1073130420641 2
Units per Pallet	20.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	5 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-3000 meters
Audible noise at 1 meter from surface of unit	40.00 dBA

Conformance

Regulatory Approvals	A-tick,C-tick,GOST,NEMKO
Standard Warranty	2 year (manufacturer's defect)

**The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of th