

技术要求Specification:

- 1、材质Material: PA66 UL94V-0;
- 2、额定电流 Current rating:1.0A AC,DC
- 3、额定电压 Voltage rating:50V AC,DC
- 4、温度范围 Temperature range:-25℃to+85℃
- 5、接触电阻 Contact resistance:≤20mΩ
- 6、绝缘电阻Insulation resistance:≥100MΩ
- 7、耐压Withstand voltage:250V AC/minute
- 8、塑件表面平整光洁,无明显的毛刺、气泡、变形、浇口拉伤、缺料等不良现象。

Plastic surface smooth and clean, no obvious burrsbubbles, distortion, gate strain, lack of material and otherundesirable phenomena.

Part No	Pin	A	B	C
WAFER-MX1.25-2PJK	2	1.25	4.30	3.00
WAFER-MX1.25-3PJK	3	2.50	5.55	4.25
WAFER-MX1.25-4PJK	4	3.75	6.80	5.50
WAFER-MX1.25-5PJK	5	5.00	8.05	6.75
WAFER-MX1.25-6PJK	6	6.25	9.30	8.00
WAFER-MX1.25-7PJK	7	7.50	10.55	9.25
WAFER-MX1.25-8PJK	8	8.75	11.80	10.50
WAFER-MX1.25-9PJK	9	10.00	13.05	11.75
WAFER-MX1.25-10PJK	10	11.25	14.30	13.00
WAFER-MX1.25-11PJK	11	12.50	15.55	14.25
WAFER-MX1.25-12PJK	12	13.75	16.80	15.50
WAFER-MX1.25-13PJK	13	15.00	18.05	16.75
WAFER-MX1.25-14PJK	14	16.25	19.30	18.00
WAFER-MX1.25-15PJK	15	17.50	20.55	19.25
WAFER-MX1.25-16PJK	16	18.75	21.80	20.50

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd		
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: MX1.25MM HOUSING	
			PAR	WAFER-MX1.25-NPJK
DECIMALS:	ANGLES:		DWN	
.X±0.30	X.*±1°		CHKD	
.XX±0.20			APVD	
.XXX±0.10			SCALE 1:1	UNIT:MM
CUSTOMER COPY		SIZE:A4		SHEET:1F1
				REV:A