

2700482

<https://www.phoenixcontact.com/us/products/2700482>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Buzzer element, continuous/pulse tone, 24 V AC/DC, max. 85 dB(A), black

Commercial data

Item number	2700482
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR07
Product key	DRL113
GTIN	4046356562003
Weight per piece (including packing)	99.5 g
Weight per piece (excluding packing)	73 g
Customs tariff number	85318070
Country of origin	DE

PSD-S AE BM2-1 85DB/W - Acoustic element



2700482

<https://www.phoenixcontact.com/us/products/2700482>

Technical data

Notes

Note on application

Note on application

Only for industrial use

Product properties

Product type

Acoustic element

Electrical properties

Maximum power dissipation for nominal condition

0.58 W

General

Input voltage

24 V AC/DC $\pm 10\%$

Nominal input voltage range

21.6 V AC/DC ... 26.4 V AC/DC

Maximum inrush current

max. 200 mA

Current consumption

25 mA

Operating time

100 %

Service life electrical

min. 5,000 h

Type of acoustic signal

Continuous/pulse tone

Signal frequency

approx. 1 Hz

Tone frequency

approx. 1.75 kHz

Volume

85

Material specifications

Color

black

Material

Polycarbonate PC

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)

-30 °C ... 50 °C

PSD-S AE BM2-1 85DB/W - Acoustic element



2700482

<https://www.phoenixcontact.com/us/products/2700482>

Classifications

ECLASS

ECLASS-11.0	27371237
ECLASS-12.0	27371237
ECLASS-13.0	27371237

ETIM

ETIM 9.0	EC001261
----------	----------

UNSPSC

UNSPSC 21.0	46171600
-------------	----------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com