GCM2165C1H101JA16# "#" indicates a package specification code.







GCM2165C1H101JA16D , GCM2165C1H101JA16J










InProduction Power train AEC Q200 Cmax. Reflow OK FlowOK ROHS REACH < List of part numbers with package codes >

Shape



Notes





Please	use	repl	acen	nents	or	Н	ecomm	end	ed.

References

Packaging	Specifications	Minimum quantity		
D	φ180mm Paper taping	4000		
J	φ330mm Paper taping	10000		

Mass (typ.)	
1 piece	6.4mg
φ180mm Reel	126g

L size	2.0 ±0.15mm
W size	1.25 ±0.15mm
Tsize	0.6 ±0.1mm
External terminal width e	0.2 to 0.7mm
Distance between external terminals g	0.7mm min.
Size code in inch(mm)	0805 (2012M)

Specifications

Capacitance	100pF±5%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	C0G(EIA)
Temperature coefficient	0±30ppm/°C
Temperature range of temperature characteristics	25 to 125°C
Operating temperature range	-55 to 125℃

1 of 1



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

