

## PCB terminal block - PTSA 1,5/ 2-3,5-Z MCBK/WH 1RZ - 1713852

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB terminal block, Nominal current: 8 A, Nom. voltage: 250 V, Pitch: 3.5 mm, Number of positions: 2, Connection method: Push-in spring connection, Mounting: Wave soldering, Color: multi-color, Soldering legs in front area, one-rowed

The figure shows a 10-position version of the product



### Key Commercial Data

Packing unit	1 STK
Minimum order quantity	1000 STK
GTIN	 4 055626 346762
GTIN	4055626346762
Weight per Piece (excluding packing)	1.440 g
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Dimensions

Length	12 mm
Pitch	3.5 mm
Dimension a	3.50 mm
Width	8.50 mm
Constructional height	13.1 mm
Height	16.7 mm
Solder pin [P]	3.6 mm
Pin dimensions	0,4 x 0,75 mm
Pin spacing	3.50 mm

## PCB terminal block - PTSA 1,5/ 2-3,5-Z MCBK/WH 1RZ - 1713852

### Technical data

#### Dimensions

Hole diameter	1 mm
---------------	------

#### General

Insulating material group	I
Rated voltage (III/2)	250 V
Nominal current I <sub>N</sub>	8 A
Solder pin surface	Sn
Flammability rating according to UL 94	V0
Number of positions	2

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values