

1150692

<https://www.phoenixcontact.com/us/products/1150692>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connecting cable, Range of articles: PRC 35, housing material: PPE, color: black, number of positions: 3, rated voltage: 690 V AC, rated current: 24 A, Connection method: Screw connection, Contact connection type: Socket/pin, This item is also available with other cable lengths. For your specific requirements, please contact your local PHOENIX CONTACT subsidiary.

Your advantages

- Time savings of 80% for startup with Plug and Play
- Locking mechanism can be unlocked manually or using a tool
- Suitable for applications in atmospheres containing salt and in direct sunlight
- Ideal for indoor and outdoor use due to weatherproof materials

Commercial data

Item number	1150692
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB03
Product key	ABLCDB
GTIN	4063151147846
Weight per piece (including packing)	2,124.5 g
Weight per piece (excluding packing)	1,962.741 g
Customs tariff number	85444290
Country of origin	PL

PRC 3-CA-MF-H07-2,5-10,0 - Connecting cable



1150692

<https://www.phoenixcontact.com/us/products/1150692>

Technical data

Notes

Order information:	This item is also available with other cable lengths. For your specific requirements, please contact your local PHOENIX CONTACT subsidiary.
--------------------	---

Product properties

Product type	Assembled installation cable
Product family	PRC 35
Number of positions	3
Connection profile	2+PE
Coding	AD

Data management status

Article revision	03
------------------	----

Insulation characteristics

Protection class	II
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	690 V
Nominal voltage ATD	690 V AC (III/2.00) in accordance with IEC 61984
	600 V AC (III/2.00) In accordance with UL 2238
	500 V AC / DC (III/2.00) in accordance with IEC 61535, when mounted
Rated surge voltage (III/2)	8 kV
Rated current	24 A (in accordance with IEC 61984)
	20 A (in accordance with IEC 61535)

Dimensions

Width	37.6 mm
Height	37.6 mm
Length	10 m

Material specifications

Color	black
Color of the housing part	black
Flammability rating according to UL 94	V0
Insulating material group	I / CTI 600
Seal material	EPDM
Housing material	PPE
Contact material	Cu
Contact surface material	silver-plated

PRC 3-CA-MF-H07-2,5-10,0 - Connecting cable



1150692

<https://www.phoenixcontact.com/us/products/1150692>

Contact carrier material	PPE
O-ring material	EPDM
Material for screw connection	PPE

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	30 °C ... 60 °C
Ambient temperature (storage/transport)	30 °C ... 60 °C
Ambient temperature (assembly)	5 °C ... 60 °C

PRC 3-CA-MF-H07-2,5-10,0 - Connecting cable



1150692

<https://www.phoenixcontact.com/us/products/1150692>

Classifications

ECLASS

ECLASS-11.0	27440109
ECLASS-12.0	27440109
ECLASS-13.0	27440109

ETIM

ETIM 9.0	EC003569
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

PRC 3-CA-MF-H07-2,5-10,0 - Connecting cable



1150692

<https://www.phoenixcontact.com/us/products/1150692>

Accessories

PRC COVER F - Protective cap

1409236

<https://www.phoenixcontact.com/us/products/1409236>



Protective cap, Range of articles: PRC 35, housing material: PPE, color: black, rated voltage: 1000, Suitable for couplings (FS)

PRC COVER M - Protective cap

1409237

<https://www.phoenixcontact.com/us/products/1409237>



Protective cap, Range of articles: PRC 35, housing material: PPE, color: black, rated voltage: 1000, Suitable for connectors (MS)

PRC 3-CA-MF-H07-2,5-10,0 - Connecting cable

1150692

<https://www.phoenixcontact.com/us/products/1150692>



PRC ED-T 1I3/2O3-4-HR-GN - T distributor

1079650

<https://www.phoenixcontact.com/us/products/1079650>



T distributor, Range of articles: PRC 35, design: T distributor, housing material: Polycarbonate fiber reinforced, color: black, rated voltage: 400 V, rated current: 32 A, Connection method: Preassembled, Contact connection type: Input: pin / outputs: socket, Alternatively, this item can be wired. For your specific requirements, please contact your local PHOENIX CONTACT subsidiary.

PRC ED-H 1I5/3O3-4-HR-GN - H distributor

1079661

<https://www.phoenixcontact.com/us/products/1079661>



H distributor, Range of articles: PRC 35, design: H-distributor, housing material: Polycarbonate fiber reinforced, color: black, rated voltage: 400 V, rated current: 32 A, Connection method: Preassembled, Contact connection type: Input: pin / outputs: socket, Alternatively, this item can be wired. For your specific requirements, please contact your local PHOENIX CONTACT subsidiary.

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com