



Part Number : 1712242015

Series Number : 171224

Product Category : High-Speed I/O  
Connectors

Product Description : zSFP+ Stacked Ganged  
Assembly with Metal Spring Fingers, 2-by-2  
with 3 Light Pipes, 80 Circuits

Status : Active

Documents & Resources

Drawings

Drawing 1712242015\_sd.pdf

3D Models and Design Files

3D Model 1712242015\_stp.zip

Electrical Model Document EE-170071-0001-001.pdf

S-Parameter Model SP-170426-1000-001.zip

Specifications


Application Specification AS-170071-0002-001.pdf

Product Specification PS-170071-0001-001.pdf

Test Summary TS-170071-0001-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Active
Category	High-Speed I/O Connectors
Series	171224
Description	zSFP+ Stacked Ganged Assembly with Metal Spring Fingers, 2-by-2 with 3 Light Pipes, 80 Circuits
Application	Module-to-Board
Component Type	Receptacle
Product Family	SFP+ and SFP Interconnect Solutions
Product Name	zSFP Plus,zSFP+
Type	Pluggable
UPC	887191132907

#### Agency

UL	E29179
----	--------

#### Electrical

Current - Maximum per Contact	0.5A
Data Rate	28.0 Gbps
Shield Type	EMI Fingers
Shielded	Yes
Voltage - Maximum	30V AC (RMS)/DC

#### Physical

Circuits (Loaded)	80
Color - Resin	Black

Durability (mating cycles max)	100
Flammability	94V-0
Gender	Female
Lock to Mating Part	Yes
Material - Metal	High Performance Alloy (HPA)
Material - Plating Mating	Gold
Material - Plating Termination	Matte Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	51.152/g
Number of Rows	2
Orientation	Right Angle
Packaging Type	Tray
Panel Mount	No
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.57mm
Pitch - Mating Interface	0.80mm
Pitch - Termination Interface	0.80mm
Plating min - Mating	0.762μm
Plating min - Termination	0.762μm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Ports	4
Temperature Range - Operating	-40° to +85°C
Termination Interface Style	Through Hole - Compliant Pin