



**+** TERMINALS & SPLICES

QUICK DISCONNECTS



✓ Active

TE CONNECTIVITY (TE)

## FF 110 REC 22-20AWG TPBR LP

FASTIN-FASTON | 110

160308-2

TE Internal Number: 160308-2

EU RoHS Compliant

EU ELV Compliant

**Terminal Type** Receptacle

**Wire Size (AWG)** 22 – 20

**Wire Size (mm<sup>2</sup>)** .3 – .6

**Mating Tab Width** 2.79 mm [ .11 in ]

**Mating Tab Thickness** .79 mm [ .031 in ]

[↓](#) **PRODUCT DRAWING**  
English

[↓](#) **3D PDF**

### DOCUMENTATION

Product Drawings

#### **LOOSE PIECE .110 SER FASTON RECEPTACLE**

PDF

**English**

CAD Files

#### **3D PDF**

PDF

**3D**

#### **Customer View Model**

2D\_DXF.ZIP

English

### Customer View Model

3D\_IGS.ZIP

English

### Customer View Model

3D\_STP.ZIP

English

## FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

### Product Type Features

**Terminates To** Wire & Cable

**FASTON** Yes

**Insulated Wire Support** Yes

**Disconnect Type** Quick Disconnect

**Insertion Force** Normal

**Wire/Cable Type** Regular Wire

**Wire Stop** No

### Configuration Features

**Connection Capacity** Single

### Body Features

**Plating Material** Tin

### Contact Features

**Terminal Type** Receptacle

**Terminal Orientation** Straight

**Crimp Type** F-Crimp

### Mechanical Attachment

**Mating Retention Type** Locking Lance

### Dimensions

**Wire Size (AWG)** 22 – 20

**Wire Size (mm<sup>2</sup>)** .3 – .6

**Mating Tab Width** 2.79 mm [ .11 in ]

**Mating Tab Thickness** .79 mm [ .031 in ]

**Accepts Wire Insulation Diameter Range** 1.3 – 2 mm [ .051 – .078 in ]

**Receptacle Stock Thickness** .25 mm [ .01 in ]

**Overall Length** 15.24 mm [ .6 in ]

### Packaging Features

**Packaging Method** Bag  
**Packaging Quantity** 1000

---

Other

**Comment** According to DIN 46340, Part 1

---

## PRODUCT COMPLIANCE



Statement of Compliance

**Statement of Compliance**

PDF

---