

Part Number: 1200698644

Product Description: Micro-Change (M12) Double-Ended Cordset with Knurled Hexnut, 3 Poles, Female (Straight) to Male (Straight), 22 AWG, Shielded WSOR Cable, 1.0m (3.28')

Length

Series Number: 120069

Product Category: Circular Industrial

Cordsets

Status: Active

Engineering Number: 883S30BS1M010

Documents & Resources

Drawings

Drawing 1200698644_sd.pdf

Product Environment Compliance

Compliance

| China RoHS | Not Reviewed |
|--------------------|--------------|
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Circular Industrial Cordsets |
| Series | 120069 |
| Description | Micro-Change (M12) Double-Ended Cordset with Knurled Hexnut, 3 Poles, Female (Straight) to Male (Straight), 22 AWG, Shielded WSOR Cable, 1.0m (3.28') Length |
| IP Rating | IP67 |
| Product Family | Brad M8 and M12 Cordsets with Knurled Hexnuts and WSOR Cable |
| Product Name | Micro-Change (M12) |
| Region | Europe |
| Type | Double Ended |
| UPC | 889056131650 |

Agency

| UL | E152210 |
|----|---------|
|----|---------|

Electrical

| Current - Maximum per Contact | 4.0A |
|-------------------------------|------|
| Voltage - Maximum | 250V |

Physical

| Cable Diameter | 5.40mm (.213") |
|---------------------------|--------------------------|
| Cable Length | 1.0m (3.28') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Micro-Change (M12) |
| Coupling Style | Knurled Hexnut, Threaded |
| Gender | Female-Male |
| Keyway | Single |
| LED Indicator | No |
| Material - Cable Jacket | TPU |
| Material - Connector Body | TPU |
| Material - Contact | Brass |
| Material - Coupling Nut | Nickel-plated Brass |

| Material - Plating Mating | Gold |
|-------------------------------|----------------------|
| Orientation | Straight to Straight |
| Poles | 3 |
| Temperature Range - Operating | -25° to +85°C |
| Wire/Cable Type | WSOR |
| Wire Size (AWG) | 22 |

This document was generated on Sep 17, 2024