

UNITRONIC® SPIRAL

Spiral cable with outer PUR sheath and overall shielding for exact impulse transmission

UNITRONIC® SPIRAL - shielded PUR spiral cable, abrasion-resistant data and control cable for use in data processing, measurement and control engineering

Info

Secure against electrical interferences

PUR outer sheath

New: Now available in cross section 0,25mm²



Interference signals



Oil-resistant



Mechanical resistance

Benefits

Overall screening prevents high frequency interference and guarantees accurate signal transmission

Extended lengths of up to 4 times the unextended spiral length

Application range

In measurement and control engineering

Wherever screened cables with smallest dimensions are required

For requirements of electronic applications

Handling and measurement equipment

Conveyor and transport systems

Product features

Abrasion and cut-resistant

Very high flexibility

Last Update (13.01.2019)

©2019 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

UNITRONIC® SPIRAL

Product Make-up

Conductor made of bare copper wires

Core insulation: Based on PVC

Screening: wrapped with braided copper wires

Outer sheath: PUR compound

Length of straight ends: 1st end = 200 mm, 2nd end = 600 mm

Versions without the mandatory LAPP designation, but with other solid lengths, end lengths and end forms available on request

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000247 ETIM 5.0 Class-Description: Spiralized cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000247 ETIM 6.0 Class-Description: Spiralized cable
Core identification code:	DIN 47100
Peak operating voltage:	250 V (not for power transmission)
Conductor stranding:	Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6
Test voltage:	1200 V
Temperature range:	Flexing: -5°C to +50°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Versions without the mandatory LAPP designation, but with other solid lengths, end lengths and end forms available on request

Article number	Number of cores and mm ² per conductor	Spiral length, extended (mm)	Spiral length, unextended (mm)	Cable diameter (mm)
73220200	2 x 0.14	400	100	4.1
73220201	2 x 0.14	800	200	4.1
73220202	2 x 0.14	1200	300	4.1
73220203	2 x 0.14	1600	400	4.1
73220204	2 x 0.14	2000	500	4.1
73220205	3 x 0.14	400	100	4.3
73220206	3 x 0.14	800	200	4.3
73220207	3 x 0.14	1200	300	4.3
73220208	3 x 0.14	1600	400	4.3
73220209	3 x 0.14	2000	500	4.3
73220210	4 x 0.14	400	100	4.5
73220211	4 x 0.14	800	200	4.5
73220212	4 x 0.14	1200	300	4.5
73220213	4 x 0.14	1600	400	4.5
73220214	4 x 0.14	2000	500	4.5
73220215	5 x 0.14	400	100	4.8
73220216	5 x 0.14	800	200	4.8
73220217	5 x 0.14	1200	300	4.8
73220218	5 x 0.14	1600	400	4.8
73220219	5 x 0.14	2000	500	4.8
73220220	6 x 0.14	400	100	5.5
73220221	6 x 0.14	800	200	5.5
73220222	6 x 0.14	1200	300	5.5
73220223	6 x 0.14	1600	400	5.5
73220224	6 x 0.14	2000	500	5.5
73220225	7 x 0.14	400	100	5.9
73220226	7 x 0.14	800	200	5.9
73220227	7 x 0.14	1200	300	5.9
73220228	7 x 0.14	1600	400	5.9
73220229	7 x 0.14	2000	500	5.9
73220230	12 x 0.14	400	100	7.2
73220231	12 x 0.14	800	200	7.2
73220232	12 x 0.14	1200	300	7.2
73220233	12 x 0.14	1600	400	7.2

Last Update (13.01.2019)
 ©2019 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03.16

Article number	Number of cores and mm ² per conductor	Spiral length, extended (mm)	Spiral length, unextended (mm)	Cable diameter (mm)
73220234	12 x 0.14	2000	500	7.2
73220235	18 x 0.14	400	100	8
73220236	18 x 0.14	800	200	8
73220237	18 x 0.14	1200	300	8
73220238	18 x 0.14	1600	400	8
73220239	18 x 0.14	2000	500	8
73220240	2 x 0.25	400	100	4.7
73220241	2 x 0.25	800	200	4.7
73220242	2 x 0.25	1200	300	4.7
73220243	2 x 0.25	1600	400	4.7
73220244	2 x 0.25	2000	500	4.7
73220245	3 x 0.25	400	100	5.3
73220246	3 x 0.25	800	200	5.3
73220247	3 x 0.25	1200	300	5.3
73220248	3 x 0.25	1600	400	5.3
73220249	3 x 0.25	2000	500	5.3
73220250	4 x 0.25	400	100	5.6
73220251	4 x 0.25	800	200	5.6
73220252	4 x 0.25	1200	300	5.6
73220253	4 x 0.25	1600	400	5.6
73220254	4 x 0.25	2000	500	5.6
73220255	5 x 0.25	400	100	6
73220256	5 x 0.25	800	200	6
73220257	5 x 0.25	1200	300	6
73220258	5 x 0.25	1600	400	6
73220259	5 x 0.25	2000	500	6
73220260	6 x 0.25	400	100	6.8
73220261	6 x 0.25	800	200	6.8
73220262	6 x 0.25	1200	300	6.8
73220263	6 x 0.25	1600	400	6.8
73220264	6 x 0.25	2000	500	6.8
73220265	7 x 0.25	400	100	7.3
73220266	7 x 0.25	800	200	7.3
73220267	7 x 0.25	1200	300	7.3

Last Update (13.01.2019)
 ©2019 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03.16

Article number	Number of cores and mm ² per conductor	Spiral length, extended (mm)	Spiral length, unextended (mm)	Cable diameter (mm)
73220268	7 x 0.25	1600	400	7.3
73220269	7 x 0.25	2000	500	7.3
73220270	12 x 0.25	400	100	8.4
73220271	12 x 0.25	800	200	8.4
73220272	12 x 0.25	1200	300	8.4
73220273	12 x 0.25	1600	400	8.4
73220274	12 x 0.25	2000	500	8.4
73220275	18 x 0.25	400	100	9.5
73220276	18 x 0.25	800	200	9.5
73220277	18 x 0.25	1200	300	9.5
73220278	18 x 0.25	1600	400	9.5
73220279	18 x 0.25	2000	500	9.5

Last Update (13.01.2019)
 ©2019 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03.16