




Home> Products > MICRO SWITCH™ Toggle Switches> TW> Product Page

12TW1-10



Actual product appearance may vary.

TW Series Toggle Switch, 2 pole, 3 position, Solder terminal, Standard Lever, Military Part Number MS27753 - 38

Features

- Qualified to MILS-83731
- Save space and weight
- SPDT and DPDT circuitry
- Temperature range:-85° F to +160° F (-65° C to +71° C)
- Sealed bushing versions
- Choice of 1/8 in. or 15/32 in. bushing
- Color tab available on 15/32 in. bushing
- UL recognized


Potential Applications

- Industrial machinery and equipment
- Military and commercial aviation
- Construction equipment
- Test instruments
- Agricultural machinery
- Process control
- Medical instrumentation

Description

MICRO SWITCH™ miniature toggle switches in two bushing sizes. Molded in terminals are plated for soldering. Momentary and maintained circuitry closures available. Special on-on-on circuitries are also available. Pull-to-unlock levers prevent accidental operation.

Supporting Documentation

-  [Accessory: Lever Sleeve](#)
-  [Terminal Identification](#)
-  [Accessory: Seals](#)
-  [Panel Cutout](#)
-  [Accessory: Nuts](#)
-  [Engineering Drawing](#)

Product Specifications	
Circuitry/Operating action	
Product Type	MICRO SWITCH™ Toggle Switch
Ampere/Voltage Range (Resistive Load)	0.1 A to 5.0 A at 0.5 Vdc to 28 Vdc,0.1 A to 5.0 A at 0.5 Vac to 115 Vac
Circuitry	DPDT
Action	3 position
Mounting	Bushing 15/32 in
Termination	Solder
Military Part Number	MS27753 - 38
Lever Type	Standard
UL/CSA Rating Code	L117: 5 A at 125 Vac
Comment	Fine silver contacts
Availability	Global
UNSPSC Code	30211908
UNSPSC Commodity	30211908 Toggle switches
Series Name	TW

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Control▼

Product Search

Part number search:

Use (\*) to expand search

Specification Search