



TE Internal #: 1-1813099-1

Housing for Female Terminals, Wire-to-Wire, 4 Position, 7 mm [.276 in] Centerline, Sealable, Black, Cable Mount (Free-Hanging)

[View on TE.com >](#)

Connectors > Automotive Connectors > Automotive Housings > Circular DIN Housings



Connector System: **Wire-to-Wire**

Number of Positions: **4**

Connector & Housing Type: **Housing for Female Terminals**

Centerline (Pitch): **7 mm [.276 in]**

Sealable: **Yes**

[All Circular DIN Housings \(64\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Circular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	On the Terminal

Configuration Features

Number of Positions	4
Number of Rows	2

Electrical Characteristics

Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V, 24 V, 42 V, 48 V

Body Features

--	--



Primary Product Color	Black
Connector & Keying Code	1

Contact Features

Contact Size	2.5mm
Contact Type	Socket
Mating Pin Diameter	2.5 mm[.098 in]

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF
Centerline (Pitch)	7 mm[.276 in]

Dimensions

Connector Height	32.9 mm[1.295 in]
Product Width	31 mm[1.22 in]
Product Length	32.9 mm[1.295 in]
Row-to-Row Spacing	6 mm, 7.8 mm[.236 in][.307 in]

Usage Conditions

Operating Temperature (Max)	70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C[158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]

Industry Standards

Degree of Protection	IP67, IP69K
UL Flammability Rating	UL 94HB

Packaging Features

Packaging Quantity	100
Packaging Method	Bag

Other



Connector Position Assurance Capable	No
--------------------------------------	----

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-967402-1
2,5MM ST-GEH KPL 4P



TE Part # 828922-1
2,5MM CAVITY PLUG FOR 5,4MM DI





TE Part # CAT-R7602-T273
ROUND CONNECTOR SYSTEM, PIN AND SOCKET



TE Part # 828920-1
EINZELADERDICHTUNG

Customers Also Bought



 TE Part #2050046-1 2POS 2.8MM SENSOR PLUG ASSY.	 TE Part #368047-1 E-S MK-2(+) 16P PLUG ASSY	 TE Part #1-1813099-3 2.5mm SOCKET HSG ASSEMBLY (BLACK 2POS)	 TE Part #493576-1 HSG 6P MICRO TIMER
 TE Part #2-2350891-1 20POS,HYBRID,PIN HSG ASSY,SLD, COD A	 TE Part #2137354-1 SECOND LOCKING DEVICE, FOR AMP-MCP 18P	 TE Part #2327042-1 2POS,MCON 1.2,TAB HSG ASSY,SLD, COD A	TE Part #5-2436634-2 SWS,AMP SUPERSEAL 1.5MM,CVTY DIA,5.5,YEL
TE Part #2438870-1 DIA 2.5MM,TERMINAL	TE Part #2441059-1 4POS,SUPERSEAL,REC HSG ASSY,SLD		

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1813099-1_A_c-1-1813099-1-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1813099-1_A_c-1-1813099-1-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1813099-1_A_c-1-1813099-1-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English