

DEUTSCH | DEUTSCH DRC

TE Internal #: DRC16-70SAE

Housing for Female Terminals, Wire-to-Wire, 70 Position, 5.49 mm [. 216 in] Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DRC

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DRC Housings



Connector System: Wire-to-Wire

Number of Positions: 70

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 5.49 mm [.216 in]

Sealable: Yes

All DEUTSCH DRC Housings (117)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing

Configuration Features

Blank Cavity Position	0
Connector Seal Code	E Seal
Number of Positions	70
Number of Rows	5

Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	250 V

Body Features

Cable Exit Angle 180°	Cable Exit Angle	180°	
Cable Exit Angle	Cabic Exit Aligic	100	



Primary Product Color	Black
Connector & Keying Code	A
Contact Features	
Contact Size	Size 16
Contact Type	Socket
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A
Mechanical Attachment	
Terminal Position Assurance	No
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PPS GF
Centerline (Pitch)	5.49 mm[.216 in]
Dimensions	
Connector Height	36.06 mm[1.421 in]
Product Width	103.99 mm[4.094 in]
Product Length	41.73 mm[1.643 in]
Row-to-Row Spacing	5.49 mm[.216 in]
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
Degree of Protection	IP68, IP6K9K
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	20mm Flame Test per Standard UL-94
Packaging Features	



Packaging Quantity	50
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-D799-CH8172 DEUTSCH DRC Housings



TE Part # CAT-J67-DSCC16 **DEUTSCH Size 16 Crimp Contacts**



TE Part # CAT-D48-SP729 **DEUTSCH Sealing Plugs**



DEUTSCH Solid Contacts



TE Part # CAT-D799-B128 **DEUTSCH DRC Backshells**



TE Part # DRC70-BT BOOT, 70P, 16SZ, PLG/REC, ST, BLK



TE Part # CAT-D799-H342 DEUTSCH DRC Headers



TE Part # 0411-336-1605 EXT TOOL, SIZE 16, 16-20 AWG, E, DRK BLU

TE Part # 0515-006-7005 PROTECT CVR, 70P, PLG, WHT, DRC16

TE Part # 0515-031-7005 WIRE ROUTER, 70P, BLK, PLG TE Part # 1062-14-0177 SOC, SF, SIZE 16, 14-18, SN/SN

Also in the Series | DEUTSCH DRC



Automotive Housings(117)



Connector Backshells(6)



Connector Strain Relief(3)



Insertion & Extraction Tools(7)



Customers Also Bought

















Documents

Product Drawings

PLG, 70P, BLK, E, A

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DRC16-70SAE_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DRC16-70SAE_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DRC16-70SAE_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

TERMINALS AND CONNECTORS

English

ICT Terminals and Connectors Catalogue

English

Product Specifications

Engineering Report

English

Housing for Female Terminals, Wire-to-Wire, 70 Position, 5.49 mm [.216 in] Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DRC



Agency Approvals

UL Report

English