

Part Number : 1722643004

**Product Description :** Ultra-Fit Tangless Terminal Position Assurance (TPA), 3.50mm

Pitch, 4 Circuits, Black

Status : Active

**Product Category:** Connector Accessories

#### **Documents & Resources**

Series Number: 172264

#### **Drawings**

Drawing 1722643004\_sd.pdf

Packaging Design Drawing 1723230005-000.pdf

### 3D Models and Design Files

3D Model 1722643004\_stp.zip

#### **Specifications**

Application Specification 1722640001-AS-000.pdf
Application Specification 1723230003-000.pdf
Product Specification 1723230001-TS-000.pdf
Product Specification 1723231000-PS-CH-000.pdf
Product Specification 1723231000-PS-ES-000.pdf
Product Specification 1723231000-PS-JP-000.pdf
Product Specification 1723231000-PS-SK-000.pdf

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

## **Part Details**

### General

Status	Active
Category	Connector Accessories
Series	172264
Description	Ultra-Fit Tangless Terminal Position Assurance (TPA), 3.50mm Pitch, 4 Circuits, Black
Component Type	Terminal Position Assurance
Product Family	Ultra-Fit Power Connectors
Product Name	Ultra-Fit
UPC	191128806152

# **Physical**

Circuits (Loaded)	4
Circuits (maximum)	4
Color - Resin	Black
Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	0.180/g
Number of Rows	1
Packaging Type	Bag
Temperature Range - Operating	-40° to +120°C

## Use with Part(s)

Description	Part Number
-------------	-------------

Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Single Row, 4 Circuits, Natural, Glow-Wire Capable	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/1722564104.html
Ultra-Fit Tangless Receptacle Housing, 3.50mm Pitch, Dual Row, 8 Circuits, Natural, Glow-Wire Capable	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/1722584108.html
Ultra-Fit Plug Housing, 3.50mm Pitch, Single Row, 4 Circuits, Natural, Glow-Wire Capable	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/2025694004.html
Ultra-Fit Plug Housing, 3.50mm Pitch, Single Row, 4 Circuits, Panel Mount, Natural, Glow-Wire Capable	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/2025694104.html
Ultra-Fit Plug Housing, 3.50mm Pitch, Dual Row, 8 Circuits, Natural, Glow-Wire Capable	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/2169454008.html
Ultra-Fit Plug Housing, 3.50mm Pitch, Dual Row, 8 Circuits, Panel Mount, Natural, Glow-Wire Capable	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/2169454108.html

This document was generated on Sep 15, 2024