

ATGBICS AFCT-5710PZ-3C1 Avago Broadcom Compatible Transceiver SFP 1000Base-LX (1310nm, SMF, 10km, Ext Temp)

Brand : ATGBICS

Product code: AFCT-5710PZ-3C1-C

Product name : AFCT-5710PZ-3C1 Avago Broadcom Compatible Transceiver SFP 1000Base-LX (1310nm, SMF, 10km, Ext Temp)



AFCT-5710PZ-3C1 Avago Broadcom Compatible Transceiver SFP 1000Base-LX (1310nm, SMF, 10km, Ext Temp)

ATGBICS AFCT-5710PZ-3C1 Avago Broadcom Compatible Transceiver SFP 1000Base-LX (1310nm, SMF, 10km, Ext Temp):

ATGBICS AFCT-5710PZ-3C1 1000Base-LX supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of 1310nm via an LC connector. Our product meets the specification of Avago AFCT-5710PZ-3C1= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

ATGBICS AFCT-5710PZ-3C1 Avago Broadcom Compatible Transceiver SFP 1000Base-LX (1310nm, SMF, 10km, Ext Temp). SFP transceiver type: Fiber optic, Maximum data transfer rate: 1000 Mbit/s, Interface type: SFP. Product colour: Silver, Housing material: Metal, Brand compatibility: Avago Technologies. Input voltage: 3.3 V, Maximum voltage: 3.5 V, Power consumption (typical): 0.8 W. Compliance certificates: RoHS, Certification: CE, FCC, RoHS. Doesn't contain: Lead



Performance		Power	
SFP transceiver type *	Fiber optic	Power consumption (typical)	0.8 W
Maximum data transfer rate *	1000 Mbit/s	Certificates	
Interface type *	SFP	Compliance certificates	RoHS
Single-mode fiber (SMF) supported	✓	Certification	CE, FCC, RoHS
Multi-mode fiber (MMF) supported	✗	Sustainability	
Fiber optic connector	LC	Sustainability compliance	✓
SFP transceiver standard	LX	Doesn't contain	Lead
Maximum transfer distance	10000 m	Operational conditions	
Wavelength	1310 nm	Minimum operating temperature	-10 °C
Ethernet LAN	✓	Maximum operating temperature	85 °C
Ethernet interface type	Gigabit Ethernet	Operating temperature (T-T)	-10 - 85 °C
Digital Diagnostics Monitoring (DDM)	✓	Storage temperature (T-T)	-10 - 85 °C
Wavelength-division multiplexing (WDM)	✗	Operating relative humidity (H-H)	5 - 95%
Features		Storage relative humidity (H-H)	5 - 95%
Product colour	Silver	Weight & dimensions	
Housing material	Metal	Width	13.4 mm
Plug and Play	✓	Depth	56.5 mm
Hot-Plug support	✓	Height	8.5 mm
Hot-swap	✓	Weight	20 g
Easy to install	✓	Packaging content	
Brand compatibility	Avago Technologies	Quantity per pack	1 pc(s)
Power		Packaging data	
Input voltage	3.3 V	Package type	Box
Maximum voltage	3.5 V	Logistics data	
		Country of origin	China



5056468759054

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-OCT-2024. Prints or copies of Information are only valid on the printed Publication date