


COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				

APPLICATION STANDARD			
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C	STORAGE TEMPERATURE RANGE
	VOLTAGE	AC 50 V	OPERATING HUMIDITY RANGE
	CURRENT	0.3 A	RELATIVE HUMIDITY : 95 % MAX (NO DEW CONDENSATION IS PERMITTED)

SPECIFICATIONS			
ITEM	TEST METHOD	REQUIREMENT	QT
CONSTRUCTION			
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING	X X
MARKING	CONFIRMED VISUALLY.		X X
ELECTRICAL CHARACTERISTICS			
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	60 mΩ MAX.	X X
INSULATION RESISTANCE	100 V DC.	100 MΩ MIN.	X —
VOLTAGE PROOF	150 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X X
MECHANICAL CHARACTERISTICS			
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE: 55.2 N MAX WITHDRAWAL FORCE: 2.3 N MIN.	X —
MECHANICAL OPERATION	50 TIMES INSERTION AND EXTRACTIONS.	1) CONTACT RESISTANCE: 70 mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X —
VIBRATION	FREQUENCY: 10 TO 55 Hz, SINGLE AMPLITUDE: 0.75 mm, — m/s ² AT 10 CYCLES FOR 3 DIRECTIONS.	1) NO ELECTRICAL DISCONTINUITY OF 1 μs MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X —
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X —
ENVIRONMENTAL CHARACTERISTICS			
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90~95 %, 96 h.	1) CONTACT RESISTANCE: 70 mΩ MAX. 2) INSULATION RESISTANCE: 100 MΩ MIN.	X —
RAPID CHAGE OF TEMPERTURE	TEMPERTURE -55→15~35→ 85→15~35°C TIME 30→ 2~ 3→ 30→ 2~ 3 min. UNDER 5 CYCLES.	3) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X —
DRY HEAT	EXPOSED AT 85 °C, 96 h.	1) CONTACT RESISTANCE: 70 mΩ MAX.	X —
COLD	EXPOSED AT -55 °C, 96 h.	2) NO DAMAGE, CRACK AND LOOSENESS OF PART.	X —
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION.	X —
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JIS C 0090)	1) CONTACT RESISTANCE: 70 mΩ MAX. 2) NO HEAVY CORROSION.	X —
RESISTANCE TO SOLDERING HEAT	REFLOW : RECOMMENDED TEMPERATURE PROFILE  TO BE TESTED UNDER THE ABOVE CONDITIONS.	NO MELTING OF RESIN WHICH AFFECTS THE PERFORMANCE OF COMPONENT.	X —
SOLDRABILITY	SOLDERED AT SOLDER TEMPERATURE, 235 °C FOR IMMERSION DURATION, 2 s.	NO PINHOLE OR DEWETTING ON SOLDERED SURFACE.	X —

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	<i>[Signature]</i> 99.10.27	<i>[Signature]</i> 99.10.27	<i>[Signature]</i> 99.10.28	<i>[Signature]</i> 99.10.28	

UNLESS OTERWISE SPECIFIED, REFER TO JIS C 5402.

NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST

HS HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET		PART NO.
	FX11LB - 92P - SV (22)		
CODE NO.(OLD)	DRAWING NO.	CODE NO.	1
CL	ELC4 - 152105 - 02	CL 573 - 0053 - 8 - 22	1