



**PennEngineering**  
**Corporate Headquarters – Danboro, PA**  
 5190 Old Easton Rd.  
 Danboro, PA 18916  
**Phone:** 215-766-8853  
**Toll-Free Phone:** 1-800-237-4736 (U.S. only)  
**Email:** [info@pemnet.com](mailto:info@pemnet.com)  
**Website:** [www.pemnet.com](http://www.pemnet.com)

## Part # KFB3-632-20ET, Broach/Flare-Mount Standoffs - Type KFB3 - Unified

No matter how sophisticated or advanced, electronic components must be attached reliably and securely if they are to deliver optimum performance. We offer several fastener products for use with PC boards to satisfy component-to-board, board-to-board, and board-to-chassis attachment needs.


Broach/flare-mount standoffs offer greater pullout performance.



### Specifications



<b>Thread Size</b>	.138-32 (#6-32)
<b>L ± .005</b>	.625 in
<b>A (Shank) Max.</b>	.090 in
<b>Sheet Thickness</b>	.050 to .065 in
<b>Hole Size in Sheet + .005 - .001</b>	.213 in
<b>B ± .003</b>	.171 in
<b>C Max.</b>	.212 in
<b>E ± .005</b>	.280 in
<b>F - Minimum Thread Length</b>	.625 in
<b>K ± .003</b>	.226 in
<b>P ± .010</b>	.040 in
<b>Min. Dist. Hole C/L to Edge</b>	.22 in
<b>Thread Specification</b>	Internal, ASME B1.1, 2B



<b>Fastener Material</b>	CDA-353 Brass
<b>Standard Finish</b>	Electro-Plated Tin, ASTM B545, Class B with Preservative Coating, Annealed
<b>CAD Supplier</b>	PennEngineering® (PEM®)