

This document was generated on 10/01/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0014564054

Status: Active

Overview: SL Modular Connectors

Description: 2.54mm Pitch SL Insulation Displacement Connector Assembly, Female, Single Row,

Version C, Front Ribs, Wire Size 28 AWG, 0.76µm Gold (Au), 5 Circuits

Documents:

<u>3D Model</u> <u>Product Specification TS-70541-001-001 (PDF)</u>
<u>Drawing (PDF)</u> <u>Packaging Specification PK-70873-0001-001 (PDF)</u>

Product Specification PS-70400-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Ribbon Cable / Wire Trap Connectors

Series <u>70400</u>

Comments Terminals Preloaded

Component Type Housing Glow-Wire Capable No

Overview <u>SL Modular Connectors</u>

Product Name SI

UPC 800753985698

Physical

Circuits (Loaded) 5
Color - Resin Black
Durability (mating cycles max) 50
Entry Angle Vertical
Flammability 94V-0
Lock to Mating Part None

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin Polyester Alloy

Number of Rows **PCB** Retention None Packaging Type Tube Pitch - Mating Interface 2.54mm Plating min - Mating 0.762um Plating min - Termination 1.905µm Polarized to Mating Part Yes Stackable Yes Surface Mount Compatible (SMC) N/A

Temperature Range - Operating -40° to +105°C
Termination Interface: Style IDT or Pierce
Wire Insulation Diameter 1.35mm max.

Wire Size AWG 28


Wire/Cable Type Discrete Wire, Ribbon Cable

Electrical

Current - Maximum per Contact 3.0A Voltage - Maximum 250V

Material Info

Engineering Number 70400-1439



Series image - Neierence oni

EU ELV

Not Reviewed

EU RoHS China RoHS

Not Reviewed REACH SVHC Not Reviewed Halogen-Free Status

Not Reviewed

For more information, please visit Contact US

China ROHS Not Reviewed ELV Not Reviewed RoHS Phthalates Not Reviewed

Search Parts in this Series

70400 Series

Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG Reference - Drawing Numbers
Packaging Specification
Product Specification
Sales Drawing

PK-70873-0001-001 PS-70400-001, TS-70541-001-001 SDA-70400-1436-1459

This document was generated on 10/01/2018

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION