

P-Channel Enhancement Mode Power MOSFET SOT-23-3

Product Summary

- $V_{DS} = -30V, I_D = -4.6A$
- $R_{DS(on)} < 55m\Omega @ V_{GS} = -10V$
- $R_{DS(on)} < 80m\Omega @ V_{GS} = -4.5V$



Features

- Advanced Trench Technology
- RoHS and Reach Compliant
- Halogen and Antimony Free
- Moisture Sensitivity Level 3

Application

- Load Switch
- PWM Application


Marking Code



(Top View)

Pin	Description
1	Gate
2	Source
3	Drain

Schematic Diagram



Absolute Maximum Ratings

(Ta=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$-V_{DS}$	30	V
Gate-Source Voltage	V_{GS}	± 20	V
Drain Current-Continuous	$-I_D$	4.6	A
Drain Current-Pulsed ^{Note1}	$-I_{DM}$	20	A
Maximum Power Dissipation	P_D	1.25	W
Junction Temperature	T_J	150	°C
Storage Temperature Range	T_{STG}	-55 to +150	°C

Thermal Characteristics

Thermal Resistance, Junction-to-Ambient ^{Note2}	$R_{\theta JA}$	100	°C/W
--	-----------------	-----	------

Electrical Characteristics

(Ta=25°C unless otherwise specified)







Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$-V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	30	--	--	V
Zero Gate Voltage Drain Current	$-I_{DSS}$	$V_{DS}=-30V, V_{GS}=0V$	--	--	1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	--	--	± 100	nA
Gate Threshold Voltage ^{Note2}	$-V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	1	1.6	3	V
Drain-Source On-Resistance ^{Note2}	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-4.1A$	--	37	55	m Ω
		$V_{GS}=-4.5V, I_D=-3A$	--	53	80	m Ω
Forward Transconductance ^{Note2}	g_{FS}	$V_{DS}=-5V, I_D=-2A$	--	6.5	--	S
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS}=-15V, V_{GS}=0V, f=1MHz$	--	530	--	pF
Output Capacitance	C_{oss}		--	70	--	pF
Reverse Transfer Capacitance	C_{rss}		--	56	--	pF
Gate Resistance	R_g	$V_{DS}=0V, V_{GS}=0V, f=1MHz$	--	12.8	--	Ω
Total Gate Charge	Q_g	$V_{DS}=-15V, I_D=-4.1A,$ $V_{GS}=-10V$	--	7	--	nC
Gate-Source Charge	Q_{gs}		--	1	--	nC
Gate-Drain Charge	Q_{gd}		--	1.4	--	nC
Switching Characteristics						
Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=-15V, R_L=15\Omega$ $V_{GS}=-10V, R_{GEN}=3\Omega$	--	14	--	nS
Turn-on Rise Time	t_r		--	61	--	nS
Turn-off Delay Time	$t_{d(off)}$		--	19	--	nS
Turn-off Fall Time	t_f		--	10	--	nS
Source-Drain Diode Characteristics						
Diode Forward Voltage ^{Note3}	$-V_{SD}$	$V_{GS}=0V, I_S=-4.6A$	--	--	1.2	V
Diode Forward Current ^{Note2}	$-I_S$		--	--	4.6	A



Note: 1. Repetitive Rating: Pulse width limited by maximum junction temperature.

2. Surface Mounted on FR4 Board, $t \leq 10$ sec.

3. Pulse Test: Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.

Typical Characteristic Curves






Package Outline

SOT-23-3

Dimensions in mm




Ordering Information

Device	Package	Shipping
TN3407PSC	SOT-23-3	3,000PCS/Reel&7inches

Conditions of Soldering and Storage

◆ Recommended condition of reflow soldering



Recommended peak temperature is over 245°C. If peak temperature is below 245°C, you may adjust the following parameters:

- Time length of peak temperature (longer)
- Time length of soldering (longer)
- Thickness of solder paste (thicker)

◆ Conditions of hand soldering


- Temperature: 300°C
- Time: 3s max.
- Times: one time

◆ Storage conditions


- **Temperature**
5 to 40°C
- **Humidity**
30 to 80% RH
- **Recommended period**
One year after manufacturing

Package Specifications

- The method of packaging



◆ Embossed tape and reel data



Reel (7")

Symbol	Value (unit: mm)
A	Ø 177.8±1
B	2.7±0.2
C	Ø 13.5±0.2
E	Ø 54.5±0.2
F	12.3±0.3
D	9.6+2/-0.3
T1	1.0±0.2
T2	1.2±0.2

