

A

B

C

D

E

F



A

B



C

D


E



Kabelführung: schwarz
cable guide: black



mit aufgesetzter
Kabelführung
(Anlieferungszustand)
with cable guide mounted
(state at time of supply)




Kabelführung verpresst
(cable guide pressed on)


siehe Verarbeitungsspezifikation
MiniBridge ERNI Electronics GmbH
according to Processing Specification
MiniBridge ERNI Electronics GmbH



Verpackt in Tray - tray packaging
Verpackungseinheit 210 Stück - packaging unit 210 pcs



Detail X
Scale 2:1




special characteristics

*ohne Hilfsmittel lösbar
*without tool unlockable

Wiedergabe sowie Vervielfältigung dieses Dokuments, Verrentung und Mitteilung seines Inhalts sind
verboten, soweit ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz.
Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Geschmackszeichenverletzung vorbehalten.
The reproduction, distribution and utilization of this document as well as the communication
of its contents to others without express authorization is prohibited. Offenders will be held liable for the
payment of damages. All rights reserved in the event of the grant of a patent, utility model or design.

Die deutsche Version dieser Zeichnung dient nur zur Erleichterung der
Handhabung. Bei Abweichungen von den englischen Original gilt das
englische Original.
The german version of this drawing has been offered for convenience only
and may deviate from the english original.
In case of any deviation the English version shall prevail.

Dimension no.				Tolerances Dim. for Information ISO 8015		 All Dimensions in mm		Scale 5:1			
Customer drawing: THIS DRAWING IS A CONTROLLED DOCUMENT.				Subject to modification without prior notice. Drawing will not be updated.				ERNI-MiniBridge Female Cable Outlet 180 IDC 04p D1,07 AWG 24/26 FLock*			
				c		19.01.2021		 TE Connectivity		©-224398-E	
Index		Date		Class		SRCA					