

LM339

DATASHEET

Specification Revision History:

Version	Date	Description
V1.0	2019/04	New
V1.1	2021/04	Modify Ordering Information
V1.2	2025/02	Modify Ordering Information
V1.3	2025/03	Add application precautions and overall typesetting.

QUAD DIFFERENTIAL COMPARATOR


DESCRIPTION

The LM339 consists of four independent voltage comparators, designed specifically to operate from a single power supply over a wide voltage range.


FEATURES

- *Signal or dual supply operation.
- *Wide operating supply range($V_{CC}=2V\sim 30V$).
- *Input common-mode voltage includes ground.
- *Low supply current drain $I_{CC}=0.8mA$ (Typical).
- *Open collector outputs for wired and connection.
- *Low input bias current $I_{bias}=25nA$ (Typical).
- *Low output saturation voltage.
- *Output compatible with TTL, DTL, and CMOS logic system.

The appearance of the product



SOP-14



DIP-14



TSSOP-14




DNF-16


Ordering Information

Product Model	Package Type	Marking	Packing	Packing Qty
LM339N(GMIC)	DIP-14	LM339 253	TUBE	1000PCS/BOX
LM339DR(GMIC)	SOP-14	LM339 253	REEL	2500PCS/REEL
LM339PWR(GMIC)	TSSOP-14	LM339 253	REEL	2500PCS/REEL
LM339QT(GMIC)	QFN-16-EP(3x3)	LM339 253	REEL	5000PCS/REEL
LM339(GMIC)	DIP-14	LM339 253	TUBE	1000PCS/BOX
LM339(GMIC)	SOP-14	LM339 B53	REEL	2500PCS/REEL
LM339(GMIC)	TSSOP-14	LM339 253	REEL	2500PCS/REEL

PIN CONFIGURATIONS



BLOCK DIAGRAM



ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

PARAMETER	SYMBOL	VALUE	UNIT
Supply Voltage	V_{CC}	+15 OR 30	V
Differential input Voltage	V_{IDiff}	30	V
Input Voltage	V_I	-0.3~30V	V
Power Dissipation	P_d	570	mW
Operating Temperature	T_{opr}	0 to+70	°C
Storage Temperature	T_{stg}	-65 to 150	°C

ELECTRICAL CHARACTERISTICS

(Vcc=5.0V,Ta=25°C,All voltage referenced to GND unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP.	MAX	UNIT
Input Offset Voltage	V_{IO}	$V_{CM}=0$ to $V_{CC}-1.5$ $V_{O(p)}=1.4V, R_s=0$		+1.5	+5.0	mV
Input Offset Current	I_{IO}			+2.3	+50	nA
Input Bias Current	I_b			57	200	nA
Input Common-Mode Voltage Range	$V_{I(R)}$		0		$V_{CC}-1.5$	V
Supply Current	I_{CC}	$R_L=\infty$		1.1	2.0	mA
Large Signal Voltage Gain	G_V	$V_{CC}=15V, R_L>15k$	50	200		V/mV
Large Signal Response Time	tres	V_i =TTL logic wing $V_{ref}=1.4V, V_{RL}=5V, R_L=5.1k$		350		ns
Response Time	tres	$V_{RL}=5V, R_L=5.1k$		1400		ns
Output Sink Current	I_{sink}	$V_i(-)>1V, V_i(+)=0V, V_{O(p)}$	6	18		mA
Output Saturation Voltage	V_{sat}	$V_i(-)>1V, V_i(+)=0V, I_{sink}=4mA$		140	400	mV
Output Leakage Current	$I_{leakage}$	$V_i(+)=1V, V_i(-)=0$ $V_{O(p)}=5V$ $V_{O(p)}=30V$		0.1	1.0	nA μA
Differential Input Voltage	$V_I(diff)$				32	V

TYPICAL PERFORMANCE CHARACTERISTICS

Fig.1 supply current




Fig.2 Input current




Fig.3 Output saturation voltage




Fig.4 Reponse time for various input overdrive negative transition




Fig.5 Reponse time for various input overdrive positive transition




Fig.6




Fig.7 voltage Follower pulse response (small signal)




Fig.8 Large signal Frequency Response




Fig.9 Output Characteristics current sourcing




Fig.10 Output Characteristics Current sinking






Fig.11 Current Limiting




Outline Dimensions

SOP-14

Unit : mm




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	8.360	8.760	0.329	0.345
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0 °	8 °	0 °	8 °

DIP-14
Unit:mm


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.710	4.310	0.146	0.170
A1	0.510		0.020	
A2	3.200	3.600	0.126	0.142
B	0.380	0.570	0.015	0.022
B1	1.524(BSC)		0.060(BSC)	
C	0.204	0.360	0.008	0.014
D	18.800	19.200	0.740	0.756
E	6.200	6.600	0.244	0.260
E1	7.320	7.920	0.288	0.312
e	2.540(BSC)		0.100(BSC)	
L	3.000	3.600	0.118	0.142
E2	8.400	9.000	0.331	0.354

TSSOP-14

Unit:mm



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.20
A1	0.05	—	0.15
A2	0.90	1.00	1.05
A3	0.39	0.44	0.49
b	0.20	—	0.28
b1	0.19	0.22	0.25
c	0.13	—	0.17
cl	0.12	0.13	0.14
D	4.90	5.00	5.10
E1	4.30	4.40	4.50
E	6.20	6.40	6.60
e	0.65BSC		
L	0.45	0.60	0.75
L1	1.00BSC		
θ	0	—	8°

Important Notice:

- Green Micro chip reserves the right to change products and documents without notice. Customers should obtain and verify the completeness of the latest technical information before placing orders. Meanwhile, Green Micro chip shall not assume any responsibility or obligation for non-officially revised documents.
- Any parameters in the entire product specification are for reference only, and actual application testing shall prevail. When customers use the products for system design, they must comply with safety regulations and independently assume the following responsibilities: selecting suitable Green Micro chip products according to application requirements; completing design verification and full-link testing of the application; and ensuring that the application complies with safety regulations or other requirements of the target market. Customers shall bear all personal or property losses caused by design defects or illegal operations, which shall have no relation to Green Micro chip.
- Green Micro chip products are prohibited from being used in scenarios such as life support, military equipment, and key aerospace applications. All accidents and legal liabilities arising from out-of-scope use shall be borne by the user, and Green Micro chip shall not be held responsible.
- All technical resources of Green Micro chip (including data sheets and reference designs) are provided "as is", without guarantee of no defects or universality, and without any express or implied warranties. The documents are only authorized for product development and research described in this document. Unauthorized use of intellectual property, public reproduction, and reverse engineering are strictly prohibited. All claims and losses caused by illegal use shall be borne by the user, and Green Micro chip shall not be liable.