

FLK 40/4X14/EZ-DR/ 200/OB32 - Cable



2298522

<https://www.phoenixcontact.com/us/products/2298522>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Round cable set; controller: Allen-Bradley SLC 500 (OB 32); connection 1: IDC/FLK socket strip (1x 40-position); connection 2: IDC/FLK socket strip (4x 14-position); cable length: 2 m

Your advantages

- System cable can be used to split 32 channels into 4 x 8 channels

Commercial data

Item number	2298522
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C421
Product key	CK221R
Catalog page	Page 475 (C-5-2019)
GTIN	4017918612412
Weight per piece (including packing)	417.3 g
Weight per piece (excluding packing)	405.4 g
Customs tariff number	85444290
Country of origin	DE

Technical data

Product properties

Product type	System cable
--------------	--------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP00
Degree of protection (Installation location)	≥ IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C (fixed installation) -10 °C ... 70 °C (flexible installation)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	≤ 2000 m

Electrical properties

Operating voltage (AC)	≤ 30 V AC
Operating voltage (DC)	≤ 60 V DC
Nominal operating mode	100% operating factor
Current (Per path, 50°C)	≤ 1 A (Uncoiled, see derating)
Current (Per path, 70°C)	≤ 0.6 A (Uncoiled, see derating)

Supported controller ALLEN-BRADLEY SLC 500

Suitable I/O card	1746 OB 32 1746 OV 32
-------------------	--------------------------

Cable/line

Cable length	2 m
--------------	-----

10X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	10
Shielded	no
Cable type	10X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	10x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	6.10 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)

FLK 40/4X14/EZ-DR/ 200/OB32 - Cable



2298522

<https://www.phoenixcontact.com/us/products/2298522>

Smallest bending radius, fixed installation	52 mm
Smallest bending radius, movable installation	98 mm
Max. bending cycles	5000
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable)
	VDE 0842, Part 332-1-2 (raw cable)
	IEC 60332-3-22 (raw cable)
	UL VW-1
	CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)
IDC/FLK40 (5)	IDC/FLK14-1 (1) = black
IDC/FLK40 (7)	IDC/FLK14-1 (2) = brown
IDC/FLK40 (9)	IDC/FLK14-1 (3) = red
IDC/FLK40 (11)	IDC/FLK14-1 (4) = orange
IDC/FLK40 (13)	IDC/FLK14-1 (5) = yellow
IDC/FLK40 (15)	IDC/FLK14-1 (6) = green
IDC/FLK40 (17)	IDC/FLK14-1 (7) = blue
IDC/FLK40 (19)	IDC/FLK14-1 (8) = violet
IDC/FLK40 (1)	IDC/FLK14-1 (9) = gray
IDC/FLK40 (37)	IDC/FLK14-1 (10) = white
IDC/FLK40 (21)	IDC/FLK14-2 (1) = black
IDC/FLK40 (23)	IDC/FLK14-2 (2) = brown
IDC/FLK40 (25)	IDC/FLK14-2 (3) = red
IDC/FLK40 (27)	IDC/FLK14-2 (4) = orange
IDC/FLK40 (29)	IDC/FLK14-2 (5) = yellow
IDC/FLK40 (31)	IDC/FLK14-2 (6) = green
IDC/FLK40 (33)	IDC/FLK14-2 (7) = blue
IDC/FLK40 (35)	IDC/FLK14-2 (8) = violet
IDC/FLK40 (3)	IDC/FLK14-2 (9) = gray
IDC/FLK40 (39)	IDC/FLK14-2 (10) = white
IDC/FLK40 (6)	IDC/FLK14-3 (1) = black
IDC/FLK40 (8)	IDC/FLK14-3 (2) = brown
IDC/FLK40 (10)	IDC/FLK14-3 (3) = red
IDC/FLK40 (12)	IDC/FLK14-3 (4) = orange
IDC/FLK40 (14)	IDC/FLK14-3 (5) = yellow
IDC/FLK40 (16)	IDC/FLK14-3 (6) = green
IDC/FLK40 (18)	IDC/FLK14-3 (7) = blue
IDC/FLK40 (20)	IDC/FLK14-3 (8) = violet
IDC/FLK40 (2)	IDC/FLK14-3 (9) = gray
IDC/FLK40 (38)	IDC/FLK14-3 (10) = white
IDC/FLK40 (22)	IDC/FLK14-4 (1) = black
IDC/FLK40 (24)	IDC/FLK14-4 (2) = brown
IDC/FLK40 (26)	IDC/FLK14-4 (3) = red
IDC/FLK40 (28)	IDC/FLK14-4 (4) = orange

FLK 40/4X14/EZ-DR/ 200/OB32 - Cable



2298522

<https://www.phoenixcontact.com/us/products/2298522>

IDC/FLK40 (30)	IDC/FLK14-4 (5) = yellow
IDC/FLK40 (32)	IDC/FLK14-4 (6) = green
IDC/FLK40 (34)	IDC/FLK14-4 (7) = blue
IDC/FLK40 (36)	IDC/FLK14-4 (8) = violet
IDC/FLK40 (4)	IDC/FLK14-4 (9) = gray
IDC/FLK40 (40)	IDC/FLK14-4 (10) = white
Cable type	Splitting cable for four modules

Connection data

Connection 1

Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	40
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Connection 2


Connection in acc. with standard	based on IEC 60603-13
Connection method	IDC/FLK socket strip
Number of connections	4
Number of positions	14
Insertion/withdrawal cycles	> 50
Pitch	2.54 mm

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

Drawings

Diagram



Maximum permissible current per path in uncoiled state

FLK 40/4X14/EZ-DR/ 200/OB32 - Cable



2298522

<https://www.phoenixcontact.com/us/products/2298522>

Classifications

ECLASS

ECLASS-11.0	27242220
-------------	----------

ETIM

ETIM 8.0	EC000237
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

FLK 40/4X14/EZ-DR/ 200/OB32 - Cable



2298522

<https://www.phoenixcontact.com/us/products/2298522>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

FLK 40/4X14/EZ-DR/ 200/OB32 - Cable

2298522

<https://www.phoenixcontact.com/us/products/2298522>



Accessories

KME - Cable marker carrier

0807083

<https://www.phoenixcontact.com/us/products/0807083>



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 x 8 mm

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com