

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



STARTER kit for the PSR-TRISAFE safety module consisting of: PSR-TRISAFE demoboard (with inputs & outputs), SAFECONF CD, Quick Start Guide, USB cable (3m) , voltage supply with international connector adapters and package inserts.

Your advantages

- Prewired starter kit including quick start guide
- Easy introduction to configurable safety technology

Commercial data

Item number	2986300
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	DN02
Product key	DNA353
Catalog page	Page 261 (C-6-2019)
GTIN	4046356503907
Weight per piece (including packing)	5.1 kg
Weight per piece (excluding packing)	3.6 kg
Customs tariff number	90230080
Country of origin	DE

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Set consists of

PSR-SAFECONF-BOX-DE - Configuration package

2986151

<https://www.phoenixcontact.com/us/products/2986151>

Configuration package for the PSR-TRISAFE safety module, consisting of the SAFECONF software, connecting cable and Quick Start Guide.



PSR-SAFECONF-BOX-EN - Configuration package

2986164

<https://www.phoenixcontact.com/us/products/2986164>

Configuration package for the PSR-TRISAFE safety module, consisting of the SAFECONF software, connecting cable and Quick Start Guide.



PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

CABLE-USB/MINI-USB-3,0M - USB cable

2986135

<https://www.phoenixcontact.com/us/products/2986135>

USB connecting cable: USB plug type A to USB plug type Mini-B; length: 3 m



PSR-SCP- 24DC/TS/M - Safety module

2986012

<https://www.phoenixcontact.com/us/products/2986012>



Freely configurable safety module with 20 safe inputs and 4 safe outputs; 4 alarm, 2 clock, and 2 ground switching outputs; can be extended with additional I/O modules, up to SIL 3, Cat.4/PL e, SIL 3, EN 50156, plug-in screw connection terminal blocks

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Technical data

Product properties

Product type	Starter kit
--------------	-------------

Electrical properties

Maximum power dissipation for nominal condition	3 W
---	-----

Dimensions

Width	37.5 mm
Height	17 mm
Depth	38 mm

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Classifications

UNSPSC

UNSPSC 21.0	39122205
-------------	----------

PSR-TRISAFE STARTER KIT - Starter kit



2986300

<https://www.phoenixcontact.com/us/products/2986300>

Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com