







Copyright FCI.



0.10
NOTE 9




RECOMMENDED PAD LAYOUT



CONFIDENTIAL

rev	ecn no	dr	date
E	S20062	JPEH	2002/06/06
F	S04-0172	JPEH	2004/08/11
G	S04-0224	KBM	2004/10/25
H	S05-0060	KBM	2005/02/28
J	S06-0236	KHL	2006/07/17
K	S10-0205	PR	2009/12/17
-	-	-	-

www.fciconnect.com			surface -  ISO 1302		tolerance std ISO 406 ISO 1101		projection 		MM 		
			TOLERANCES UNLESS OTHERWISE SPECIFIED								
Dr	JPEH	2002/06/06	ANGULAR	LINEAR	0.X	±-	size A3	Scale 10:1			
Eng	JPEH	2004/08/11			0.XX	±0.25					
Chr	KH LEE	2009/12/17	0°	±3°	0.XXX	±-	ECN		S10-0205		
Appr	JOEY NG	2009/12/17	Product family				MINITEK	Spec ref -			
			title POL. MINITEK II SMT STR HEADER (DUPLEX)				dwg no 61698				Rev. K
			catalog no -				CUSTOMER		sheet 1 of 2		



Copyright FCI.

A

B

C

D

PRODUCT NO. SEE NOTE 8	POS	POL. POS	DIM X	DIM Y
61698-X01	2X22	20	42	44
-X02	2X13	1	24	26
-X03	2X16	3, 4, 5, 6, 32	30	32

NOTES:

- MATERIAL:
BODY : HIGH TEMPERATURE THERMOPLASTIC UL 94V-0 BLACK
PIN : COPPER ALLOY
- TOLERANCE UNLESS OTHERWISE NOTED ± 0.25
- DIM 1.0 APPLIES TO MOLDED SIDE(S) ONLY.
IF SIDE(S) ARE BROKEN, DIM 1.5 MAX APPLIES.
- RECESS APPLIES TO MOLDED SIDE(S) ONLY.
- PLATING ON MATING LENGTH:
-3XX --- 0.38 μ m Au OVER 1.27 μ m MIN NICKEL UNDERPLATE.
-5XX --- 0.38 μ m PdNi W Au FLASH OVER 1.27 μ m MIN NICKEL UNDERPLATE.
-6XX --- 0.76 μ m PdNi W Au FLASH OVER 1.27 μ m MIN NICKEL UNDERPLATE.
- SOLDER TAIL PLATING:
a) SOLDER TAIL OF P/N:61698-XXX IS 3.81 μ m MIN TIN/LEAD (90/10) PLATED OVER 1.27 μ m MIN NICKEL UNDERPLATE.
b) SOLDER TAIL OF P/N:61698-XXXLF IS 2.54 μ m MIN 100% MATTE TIN PLATED OVER 1.27 μ m MIN NICKEL UNDERPLATE (LEADFREE).
- PACKAGING:
a) STANDARD PACKAGING IN PLASTIC BAG.
b) SPECIFY 61698-XXXT FOR TUBE PACKAGING.
c) SPECIFY 61698-XXXTR FOR TAP AND REEL PACKAGING.
A PICK-UP CAP IS PROVIDED IN THE CENTRE OF THE PRODUCT (SEE FIG.1) FOR PICK AND PLACE APPLICATION.
d) SPECIFY 61698-XXXTC FOR TUBE PACKAGING WITH PICK-UP CAP IN CENTRE OF PRODUCT(SEE FIG.1).

PICK-UP CAP





FIG. 1
NOTE 7 (c)&(d)
SCALE 5:1

- PART NUMBER INFORMATION
61698-XYZZLF
LEAD FREE. SEE NOTES 6b, 12
TYPE OF PACKAGING SEE NOTE 7
DASH NUMBER
PLATING AT MATING. SEE NOTE 5
BASE NUMBER
- COPLANARITY OF SOLDER LEADS TO BE WITHIN 0.10mm.
- POLARISED BY OMISSION OF PINS. REFER TO TABLE FOR POL. POS.
- THE HOUSING WILL WITHSTAND EXPOSURE TO 255°C PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
- THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- A $\triangle K$ SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.

CONFIDENTIAL

www.fciconnect.com			surface ISO 1302	tolerance std ISO 406 ISO 1101	projection size A3	MM Scale 10:1
			TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	JPEH	2002/06/06	ANGULAR	LINEAR	0.X	±
Eng	JPEH	2004/08/11			0.XX	±0.25
Chr	KH LEE	2009/12/17	0° ±3°		0.XXX	±
Appr	JOEY NG	2009/12/17	Product family		MINITEK	Spec ref -
POL. MINITEK II			dwg no			Rev.
SMT STR HEADER (DUPLEX)			61698			K
catalog no			CUSTOMER			sheet 2 of 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[61698-302TRLF](#) [61698-302TR](#) [61698-301TCLF](#) [61698-302LF](#) [61698-301TR](#) [61698-301TRLF](#) [61698-302T](#) [61698-302TC](#) [61698-502T](#) [61698-502TR](#) [61698-602TC](#) [61698-602TCLF](#) [61698-301TC](#) [61698-302](#) [61698-303](#) [61698-602TRLF](#)