

ROHS PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	PART NUMBER	PART NUMBER
09	30.81	24.99	16.96	16.21	10.96	D09S90C4GV00LF	D09S90C6GV00LF
15	39.14	33.32	25.18	24.54	19.18	D15S90C4GV00LF	D15S90C6GV00LF
25	53.03	47.04	39.12	38.25	33.12	D25S90C4GV00LF	D25S90C6GV00LF
37	69.32	63.50	55.68	54.71	49.68	D37S90C4GV00LF	D37S90C6GV00LF
						gold flash	0.76» gold

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0001

mat'l. code				surface ISO 1302	tolerance ISO 406 ISO 1101	projection	product family D-SUB
ltr	ecn no	dr	date	tolerances unless otherwise specified			title
B	-	JAR	1996-07-24	angles	linear	mm	FEMALE CONNECTOR DELTA LOW PROFILE
C	LS05-004	MPE	2005-02-08				STRAIGHT PRESS-FIT
D	LS06-0097	LGO	2006-07-29	0°±2°		scale 2:1	
E	LS06-0140	LGO	2006-09-25	dr	PESSON	1995-10-03	dwg no
F	ELX-I-24020	AAB	2016-06-06	engr	MITHUN PAUL	2016-06-06	sheet 1 of 1
				chr	ATHUL A.B	2016-06-06	size
				appd	BIJU K PAUL	2016-06-06	A3
sheet index	revision	F					type Product Customer Drawing
	sheet	1					

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[D09S90C6GV00LF](#) [D15S90C6GV00LF](#) [D25S90C6GV00LF](#) [D37S90C4GV00LF](#) [D09S90C6GV00](#) [D15S90C6GV00](#)
[D25S90C6GV00](#) [D37S90C4GV00](#)