

PRODUCT NUMBER

10129379 - X YY XXX X LF

LEAD FREE OPTION
(SEE NOTES 7)



PACKAGING OPTIONS
(SEE NOTE 3)

INDICATES DIFFERENT MATING LENGTH
TAIL LENGTH AND OTHER OPTIONS
(SEE TABLE IN SHEET 2)



NO. OF
POSITIONS
(SEE NOTE 2)

PIN PLATING
(SEE SHEET 2)

BASE PART NO.



DETAIL P
TYP BOTH ENDS



.100±.003 [2.54±.08]
TYP. NON-ACCUMULATIVE
Ø.040±.003 [1.02±.08]
TYP.

RECOMMENDED HOLE PATTERN

mat'l. code SEE NOTES 1		surface ISO 1302 ✓	tolerance ISO 406 ISO 1101	projection INCH/MM	product family ECONOSTIK
ltr	ec	n	odr	date	title
A	NEW	ZK	04/23/14	angles	ECONOSTIK HEADER
B	BLX-N-18529	ZK	08/14/14	linear	.100/2.54cc SR R/A
				0°±2°	
				dr	ZK HU 04/23/14
				enr	ZK HU 04/23/14
				chr	RICK BIAN 04/23/14
				app	RICK BIAN 04/23/14
sheet	revision	B	B		dwg no
index	sheet	1	2		10129379
					type Product Customer Drawing

1		2		3							4	5		6
PRODUCT NUMBER	MATING LENGTH		TAIL LENGTH		BENDING DIMENSION		PIN PLATING CODES:							
	DIM F	DIM F	DIM G	DIM G	DIM H	DIM H	10129379-9YYXXXLF 1u"/0.025u MIN Au OVER 50u"/1.27u MIN Ni							
	ENGLISH	METRIC	ENGLISH	METRIC	ENGLISH	METRIC								
10129379-XY001XLF	0.230	5.84	0.120	3.05	0.060	1.52								
10129379-XY002XLF	0.230	5.84	0.090	2.29	0.060	1.52								
10129379-XY003XLF	0.318	8.08	0.120	3.05	0.060	1.52								
10129379-XY004XLF	0.318	8.08	0.090	2.29	0.060	1.52								

NOTES:

1. MATERIAL
- BODAY MATERIAL: HIGH TEMPERATURE THERMOPLASTIC.

FLAME UL94-V0, BLACK.

PIN MATERIAL: COPPER ALLOY.
2. ANY NUMBER OF POSITIONS N FROM 1 TO 36.
- PRODUCT MAYBE CUTTING TO POSITION,

THE CUTTING PLASH IS 0.02[0.51] MAX.
3. PACKING STYLE DEFINITION.
- B: PACKED WITH POLY BAG

T: PACKED WITH TUBE

A: PACKED WITH TAPE AND REEL WITH PICK UP CAP

C: PACKED WITH TAPE AND REEL WITHOUT PICK UP CAP
4. TWO SIDES OF PIN TIPS NOT PLATED, TYPICAL BOTH ENDS.
5. 2LBS/0.9KG MIN PIN RETENTION IN EITHER DIRECTION BEFORE REFLOW.
6. THE OAL DON'T EXCEED 1 INCH / 25.4MM.
7. ADD LF AT THE END OF PART NUMBER IS FOR LEAD FREE.
8. THESE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
9. PRODUCT SPECIFICATION: GS-12-1223.
10. THIS PRODUCT WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 20 SECONDS IN WAVE SOLDER, INFRA-RED OR VAPOR PHASE SOLDER PROCESS.

mat'l. code			surface		tolerance		projection		product family	
SEE NOTES 1			ISO 1302 ✓		ISO 406 ISO 1101				ECONOSTIK	
l	tr	ec	n	o	d	r	date		title	
B									ECONOSTIK HEADER	
									.100/2.54cc SR R/A	
									dwg no	
									sheet2 of 2	
									size	
									10129379	
									A3	
									type	
									Product Customer Drawing	
sheet	revision									
index	sheet									

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

<u>10129379-906004BLF</u>	<u>10129379-907001BLF</u>	<u>10129379-907003BLF</u>	<u>10129379-903002BLF</u>	<u>10129379-912003BLF</u>
<u>10129379-906003BLF</u>	<u>10129379-907004BLF</u>	<u>10129379-910001BLF</u>	<u>10129379-916002BLF</u>	<u>10129379-902001BLF</u>
<u>10129379-903004BLF</u>	<u>10129379-910003BLF</u>	<u>10129379-907002BLF</u>	<u>10129379-912001BLF</u>	<u>10129379-912002BLF</u>
<u>10129379-912004BLF</u>	<u>10129379-910004BLF</u>	<u>10129379-902003BLF</u>	<u>10129379-902004BLF</u>	<u>10129379-903001BLF</u>
<u>10129379-904003BLF</u>	<u>10129379-909002BLF</u>	<u>10129379-905003BLF</u>	<u>10129379-908004BLF</u>	<u>10129379-906002BLF</u>
<u>10129379-904004BLF</u>	<u>10129379-905001BLF</u>	<u>10129379-902002BLF</u>	<u>10129379-916001BLF</u>	<u>10129379-916003BLF</u>
<u>10129379-908002BLF</u>	<u>10129379-916004BLF</u>	<u>10129379-936001BLF</u>	<u>10129379-936003BLF</u>	<u>10129379-936002BLF</u>
<u>10129379-936004BLF</u>	<u>10129379-904002BLF</u>	<u>10129379-906001BLF</u>	<u>10129379-903003BLF</u>	<u>10129379-904001BLF</u>
<u>10129379-905004BLF</u>	<u>10129379-908001BLF</u>	<u>10129379-908003BLF</u>	<u>10129379-910002BLF</u>	<u>10129379-909001BLF</u>
<u>10129379-920001BLF</u>	<u>10129379-920002BLF</u>	<u>10129379-905002BLF</u>		