




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Extraction Force	7 – 100 Newton
Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	23 mm[.905 in]
Compatible Insulation Diameter Range	2.2 – 3.4 mm[.086 – .134 in]
Wire Size	.51 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	1000
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 928901-3 PL 250 REC TERMINAL 17-13 AWG TPBR LP	 TE Part # 171809-2 POSITIVE LOCK (PL) HOUSING	 TE Part # 928901-4 PL 250 REC TERMINAL 17-13 TPPB LP	 TE Part # 171809-1 POSITIVE LOCK (PL) HOUSING
 TE Part # 755342-1 DAHT POS LOCK REC CONT 20-14 ASSY	 TE Part # 1337265-1 POS LOCK RECEPTACLE GOLD	 TE Part # 784640-1 EXT TOOL FOR POS LOCK MKI	 TE Part # 927853-8 PL 250 REC 20-17 AWG AgBR
 TE Part # 752940-1 CRIMPING JAW HEAD ASSY			

Also in the Series | Positive Lock 250



Automotive Terminals(1)



Crimp Terminal Housings(190)



Insertion & Extraction Tools(3)



Insulation Boots & Sleeves(4)



Quick Disconnects(185)

Customers Also Bought



TE Part #2-179553-2
Receptacle and Tab Housing: 5.08 mm Pitch, 250-600V



TE Part #2-917337-2
DYNAMIC 3200 HDR ASSY



TE Part #178323-3
DYNAMIC D3100D HDR V 6P ASSY AU076



TE Part #60620-4
CMNL PIN 20-14 TPPHBZ L/P

Documents

Product Drawings

PL 250 REC 12-10 AWG 0.406 X 42.3

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_170265-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_170265-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_170265-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.



Product Specifications

Product Specification

English

1-Position, Positive Lock Connector

English