HellermannTyton

Specification Sheet

Part Number: 558-00342

Pre-printed header striped continuous vinyl rolls come in different header colors, providing a variety of printing options.

Very Policy

(7.20 or strain)

(8.20 or strain)

(9.20 or strain)

(1.20 or strain)

(1.20 or strain)

(2.20 or strain)

(3.20 or strain)

(3.20 or strain)

(4.20 or strain)

(5.20 or strain)

(6.20 or strain)

(7.20 or strain)

(8.20 or strain)

The headers can be printed with various ARC FLASH, WARNING And CAUTION headlines to meet OSHA safety standards for identifying electrical panels and equipment.

Signs can be designed in TagPrint Pro labeling software and printed with any HellermannTyton thermal transfer printing system with optional cutter attached.

Thermal Transfer Adhesive Labels, Solid Color Continuous Roll, 2.0 x 250', UV Stable VL, Green, 250 ft/roll

Article Number 558-00342

Type HT2GN250

Color Green (GN)

Quantity Per reel

Product Description

Continuous Vinyl Labels are made with UV-stable materials for long outdoor life. The labels are extruded in the actual color and not colored using surface inks for long-term fade resistance. Vinyl labels are provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems. Good for all surface types except powder coat painted or low surface energy substrates such as polyproylene. Test on these surfaces before approving.

Short Description	Thermal Transfer Adhesive Labels, Solid Color Continuous Roll, 2.0 x 250', UV Stable VL, Green, 250 ft/roll
Global Part Name	HT2GN250-1500-GN
Length L (Imperial)	250.0
Length L (Metric)	76.20
Variant	3.2mil, 50lb bleached kraft paper
Width W (Imperial)	2.0
Width W (Metric)	50.8
Thickness T (Metric)	64.0
Width of Liner (Metric)	50.8
Width of Liner (Imperial)	2.0
Material	Type 1500, Vinyl, UV-stabilized, glossy (1500)
Material Shortcut	1500

Acrylic

No

Adhesive

Halogen Free

UV Resistant (Yes/No) Yes

Adhesive Operating Temperature -40°F to +180°F (-40°C to +82°C)

Operating Temperature -40°F to +180°F (-40°C to +82°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant Yes

Certification/Specification NEC2011 NEC2017 NEC2014 NEC2020 NEC2023

Package Quantity (Imperial) 250

Package Quantity (Metric) 76.20

Customs Number 3919102055

Labels per Column 1

Labels per Row 1

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).