



Technical Data

22.01.2024

Heat shrinkable tubing 2:1 - flexible and coloured
HFT-A - self extinguishing

HFT-A-6.4/3.2

Article Number 305-06409



Material: Polyolefin, cross-linked (PO-X)
Colour: White (WH)

Supplied Ø D min.: 6.4 mm
Recov. Ø d max.: 3.2 mm
Wall (WT): 0.60 mm
Shrink Ratio: 2:1
Longitudinal Change After Shrinkage: -5% max.
Min. Shrink Temperature - °C: +135 °C

Test Method

Flammability: UL 224 VW-1
Operating Temperature : -55 °C to +135 °C
Heat Shock Test: 4h/200°C
Tensile Strength at Heat Shock: 13 MPa
Elongation at Heat Shock: 390 %
Behaviour At Low Temperature: not cracking

IEC 60684-2

Dielectric Strength: 21 kV/mm
Insulation Class: B (VDE 0530)
Tensile Strength: 14 MPa
Elongation at break: 400%
Specifications: CLASS 903201, UL 224, VG 95343-5:2016-10

IEC 60684-2

IEC 60684-2

IEC 60684-2



We assume no responsibility that the Product will be used for the intended purpose, this is beyond our control. It's up to the customer to check the suitability for a specific application by means of tests. Technical changes and errors reserved