



Wire Protection & Management > Wiring Ducts & Accessories > Wiring Ducts & Covers > Wiring Duct Covers: PVC, Gray, 2 meters [2000mm]



Wiring Duct Product Type: **Cover**

Primary Product Material: **PVC**

Product Height: **9.1 mm [.358 in]**

Product Length: **2000 mm [78.74 in]**

Product Width: **60 mm [2.362 in]**

[All Wiring Duct Covers: PVC, Gray, 2 meters \[2000mm\] \(6\)](#)

Features

Product Type Features

Wiring Duct Product Type	Cover
--------------------------	-------

Body Features

Primary Product Color	Gray
Primary Product Material	PVC

Dimensions

Product Height	9.1 mm[.358 in]
Product Length	2000 mm[78.74 in]
Product Width	60 mm[2.362 in]

Usage Conditions

Operating Temperature Range	-5 – 60 °C[23 – 140 °F]
-----------------------------	-------------------------

Packaging Features

Packaging Quantity	3
--------------------	---



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-Z62-W1-DP
PVC Wiring Duct: 2 meters, Gray
Color, Flame-Retardant

Customers Also Bought

1SET411203R0000

Cover, PVC, Height 9.1 mm [.358 in], Length 2000 mm [78.74 in], Width 60 mm [2.362 in], -5 – 60 °C [23 – 140 °F]



 TE Part #T4111002041-000 M12,MALE,STRAIGHT,A CODE,4P, PG9,GOLD	 TE Part #2065124003 HFT5000-20/10-0-SP	 TE Part #1SET411010R0000 PVC Wiring Duct: 2 meters, Gray Color, Flame-Retardant	 TE Part #1SET411202R0000 WD-1-CP-GR040
 TE Part #926893-1 UNIV.M-N-L.SOCKET CONTACT	 TE Part #350720-1 09P UMNL PLUG HSG	 TE Part #T4151199L25-001 RPC-M12L-5MS-0.5-PVC 14AWG GY	 TE Part #1-1414632-0 V23132B2002X025

Documents

Product Drawings

WD-1-CP-GR060

French

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SET411203R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SET411203R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SET411203R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Infographic - entrelec ews-linecard

English

Datasheet - Entrelec Electrical-Solutions

Datasheet - ENTRELEC-wiring-duct-DS

English

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

1SET411203R0000

Cover, PVC, Height 9.1 mm [.358 in], Length 2000 mm [78.74 in], Width 60 mm [2.362 in], -5 – 60 °C [23 – 140 °F]



English

[Essential Entrelec Terminal Blocks](#)

Japanese

[Agency Approvals](#)

[Agency Approval Document](#)

English