

SPECIAL

3AB Very Fast-Acting Type



For protection of silicon controlled rectifiers and similar solid-state devices.

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Ampere Rating	Opening Time
100%	1-30	4 hours, Minimum
250%	1-10	.2 seconds, Maximum
250%	12-30	1 second, Maximum

APPROVALS: Recognized under the Components Program of Underwriters Laboratories.



FUSE DIMENSIONS:
Diameter: 1/4"
Length: 1 1/4"

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
322 001	1	250
322 1.25	1 1/4	250
322 002	2	250
322 003	3	250
322 004	4	250
322 005	5	250
322 006	6	250
322 007	7	250
322 008	8	250
322 009	9	250
322 010	10	250
322 012	12	65
322 015	15	65
322 020	20	65
322 025	25	65
322 030	30	65

3AB Indicating Fast-Acting Type



ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
110%	4 hours, Minimum
135%	1 hour, Maximum
200%	10 seconds, Maximum

APPROVALS: Listed by Underwriters Laboratories through 5 amperes.

INDICATING PIN: Extends a minimum of 3/16" from the end of the fuse when the fuse is blown. Pin is silver plated.



FUSE DIMENSIONS:
Diameter: 1/4"
Length: 1 1/4"

NOTE: To order fuses with red indicating pin, change 334 to 336.

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
334.750	3/4	125
334 001	1	125
334 01.5	1 1/2	125
334 002	2	125
334 003	3	125
334 004	4	125
334 005	5	125
334 006	6	125
334 008	8	125
334 010	10	125
334 012	12	125
334 015	15	125
334 020	20	32

obsolete

336 8A and higher

Indicating/Alarm Fast-Acting Type



For telecommunications equipment and similar applications.

ELECTRICAL CHARACTERISTICS:



% of Ampere Rating	Opening Time
100%	10 minutes, Minimum
150%	5 minutes, Maximum

APPROVALS: Recognized under the Components Program of Underwriters Laboratories.

INDICATOR FLAG: Color-coded to indicate ampere rating.

BODY: Black phenolic with UL 94V0 flammability rating.

CONTACTS: Bright alloy-plated beryllium copper.



NOTE: Mating 402 001 fuse-holder available: see fuseholder section.

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Flag Color Code	AC Voltage Rating	DC Voltage Rating
401.180	18/100	Yellow	125	60
401.250	1/4	Violet	125	60
401.500	1/2	Red	125	60
401.650	65/100	Black	125	60
401.750	3/4	Brown	125	60
401 001	1	Gray	125	60
401 1.33	1 1/3	White	125	60
401 01.5	1 1/2	Yellow/White	125	60
401 002	2	Orange	125	60
401 003	3	Blue	125	60
401 03.5	3 1/2	Blue/White	125	60
401 004	4	Brown/White	125	60
401 005	5	Green	125	60
401 07.5	7 1/2	Black/White	125	60
401 010	10	Red/White	125	60