



RoHS

MAPX

MODIFICATION

DRW

DATE



PCB LAYOUT

特性: Specifications:

电气: Electrical:

1. 接触阻抗: Contact Resistance:
30 milliohms MAX
2. 耐电压: Dielectric With Standing Voitage:
500 V AC AT Sea Levol
3. 绝缘阻抗: Lnsulation Resistance:
1000 MEGA ohms MIN

机构: Mechanical:




1. 结合力: Mating Force:
35 N MAX 最大 35 N
2. 拔出力: Unmating Force:
8 N MIN 最少 8 N

材料: Matorial:

1. 塑胶: 黑色PBT.
2. 端子: Contact: C2680, T=0.25±0.01
3. 外壳: Shell: SPCC, T=0.3±0.01

电镀: Finish:

1. 端子: Contact: Piated Gold in Mating Area:
Tin/Lead On Solder Talls. 接触点镀金1唛, 脚镀锡100唛
2. 外壳: Shell:
Nickel Plating . 镀镍80唛
额定电流2.5A, 盐雾24H, 镀锡部分12H



产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.25	X.	±5.°
.X	±0.20	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

深圳市精拓金电子有限公司
Shenzhen Jing Tuo Jin Electronics Co., Ltd.

单位 UNITS	MM	制图 DRAWING	尹先华	制图料号 PRODUCT PART NO.	912-122A102AD10200
比例 SCALE	1:1	审核 CHKD	郭治富	产品名称 PRODUCT NO.	AF10.6短体前两脚无边铜壳PBT黑胶8.2 DIP
日期 DATE	2021-04-14	核准 APPD	黄国荣	角法 VIEW	版本 VER

A0