

DIGITUS 4K HDMI Audio Extractor

DS-40132

EAN 4016032374084



4K HDMI to HDMI/3.5mm/Toslink Audio Converter, 4K compatible small housing, black

With a Digitus HDMI audio extractor, you can split the audio signal from the HDMI signal and play it over your speakers, surround system, amplifier, or headphones – you get to decide which output device to use and receive the best sound quality each and every time. The integrated switch makes it possible to select between 2.1 channel via a 3.5-mm jack and 5.1 channel via TOSLINK. The integrated HDMI amplifier also enhances the video signal (Full HD up to 30 m, 4K up to 20 m). The extractor is powered via the HDMI cable and thus requires no separate power supply; power can also be supplied via the enclosed USB cable.

- Inputs: 1 x HDMI jack, 1 x USB as an optional power source
- Outputs: 1 x 3.5 mm audio jack, 1 x Toslink SPDIF
- Video resolutions of up to 4K at 30hz possible
- Supports CEC and HDCP
- Audio output (2.1 stereo) via HDMI or 3.5 mm jack
- Audio output (5.1 stereo) via Toslink SPDIF

- Integrated HDMI amplifier ensures signal conditioning/enhancement
- Compatible with all HDMI versions
- Maximum HDMI bandwidth: 300 MHz
- HDMI transfer rate: 3.0 Gbps
- Optional power supply via USB if power supplied via HDMI not adequate
- No software or driver installation required
- Supports HDMI audio formats: DTS-HD/Dolby TrueHD
- Lightweight, compact housing
- Color: black
- Weight: 40 g
- Dimensions: 66 x 55 x 20 mm (L x W x H)

Lieferumfang

- Audio extractor
- Mini USB power cable
- User manual

Logistische Daten						
	Anzahl (Stück)	Gewicht (kg)	Tiefe (cm)	Breite (cm)	Höhe (cm)	cm³
Karton-VPE	200	14,00	26,00	47,00	55,00	67.210,00
Innen-VPE	1	0,07	13,50	10,70	5,00	722,25
Einzel-VPE	1	0,07	13,50	10,70	5,00	722,25
Netto einzeln ohne VP	1	0,42	5,40	6,00	2,00	64,80



Weitere Anwendungsbilder:

