





RoHS



RECOMMENDED PCB LAYOUT
GENERAL TOLERANCES: ±0.05

电气特性:Electrical:

- 额定电流: Current Rating
1.5A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触阻抗:Contact Resistance
30 milliohms MAX
- 耐电压:Dielectric Withstanding Voltage:
500 V AC AT Sea level
- 绝缘阻抗:Insulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force:3.57kgf (MAX)
Unmate force:0.7kgf (MIN)
 - 端子保持力: Terminal Retention
1.0kgf (MIN)
 - 寿命: 1500次
- 原材料:Material:
- 塑胶:Housing:pbt/LCP
 - 端子:Contact:Copper Alloy C2680
 - 外壳:Shell:SPCC/C2680
- 电镀:Finish:
- 端子Contact: Au G/F u" Plated on contact area
Tin50u" Plated on solder area
 - Nickel 50u" Plated underplating over all.
 - 外壳Shell: Nickel 50u"Min plating over all.

产品图

PIN NUMBER	SIGNAL NAME
1	V BUS
2	D-
3	D+
4	GND

公差一览表

TOLERANCE UNLESS OTHERWISE				単位 UNITS
X.	±0.35	X.	±5°	比例 SCALE
.X	±0.30	.X°	±2°	
.XX	±0.25	.XX°	±1°	
				日期

深圳市精拓金电子有限公司

单位	MM	制图	L S S	产品料号	906-151A10210200		
UNITS		DRAWING		PRODUCT PART NO.			
比例	1:1	审核	G Z F	产品名称	AF1.4.0 漏油箱体三直脚有边壳PBT 漏胶		
SCALE		CHKD		PRODUCT NO.			
日期	2021/03/10	核准	黄国荣	角法			
DATE		APPRD		NEW			
					版本	AO	
					VER		

您正在使用 ZWCAD 2022 个人版，不得用于商业用途，详情请咨询4005-182-598。