

| COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE | COUNT | DESCRIPTION OF REVISIONS | BY | CHKD | DATE |
|-------|--------------------------|----|------|------|-------|--------------------------|----|------|------|
| △     |                          |    |      | ..   | △     |                          |    |      | ..   |
| △     |                          |    |      | ..   | △     |                          |    |      | ..   |
| △     |                          |    |      | ..   | △     |                          |    |      | ..   |

A B C D E F

1 2 3 4 5 6 7 8

TO PCK

6.2±0.3 6±0.2 30±0.2 28.5±0.2 0.2±0.05 0.5±0.05 (0.5) 37±0.3 32.8±0.1 (0.6) 1.65±0.3 (φ0.8) 32.8±0.05 30±0.05 28.5±0.05 0.5±0.03 2.15±0.05 φ0.9±0.05 2.2±0.1 3 4.5±0.1 4.8±0.1 5.0±0.1 φ1±0.05 0.7±0.03 (LAND PATTERN) 0.6±0.03 (METAL MASK) 0.3±0.03 (LAND PATTERN) 0.25±0.03 (METAL MASK)

RECOMMENDED LAND PATTERN DIMENSION OF PCB

NOTES 1 SMT LEAD-COPLANARITY:0.1 MAX.  
2 THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.  
3 MAKE SURE WIDTH OF PATTERN IS WITHIN THAT OF LAND .OR LEAD MAY TOUCH PATTERN. (THIS APPLIES TO HATCHED AREA.)

CONTACT AREA: GOLD (0.1μm) OVER NICKEL  
LEAD: GOLD FLASH OVER NICKEL  
2 PHOSPHOR BRONZE  
1 LCP  
NO. MATERIAL FINISH, REMARKS NO. MATERIAL FINISH, REMARKS  
CODE NO. (OLD) CL  
DRAWING NO. EDC3-152118  
SCALE 5 : 1  
UNITS mm  
PART NO. FX11LA-116S-SV  
CODE NO. CL573-0144-1  
HIROSE ELECTRIC CO.,LTD.

1 2 3 4 5 6 7 8

TO PCK

CL573-0144-1

FORM NO.229