

1

2

3

4

5

6

7

8

SAMZO

REAC/ROHS

REV	ECN NO	DESCRIPTION	DESIGN	APPROVAL	DATE
A1	NEW	Replace frame			2018.06.12

technical parameters

- .Impedance: 50Ω
- .Frequency range: 0 - 12.4G
- .Voltage standing wave ratio: For straight flexible cable, less than 1.15±0.02f (GHz)
- .Operating voltage: 335V max
- .Dielectric withstand voltage: 1000Vrms
- .Contact resistance: Inner conductor less than 3 mOhm, outer conductor less than 2 mOhm
- .Insulation resistance: greater than 500 MΩ
- .Durability: 500 times
- .Operating temperature: -65 to +165 (For PE CABLE, -40 to +85)
- Standards: MIL-C-39012, IEC169-15, CECC22110
- Salt Mist(Time):48H

SMA-KWE-199-W4-X

- Surface treatment镀层:0-镀金/1-镀镍
- Pin position脚位:W4-正脚4pin
- Length体长:20mm
- Product number编号:KWE
- Product series系列:SMA同轴射频天线座

1. 8螺母+1.0垫片配件

ITEM	DESCRIPTION	MATERIAL	QTY	FINSH/COLOR					
C	插孔	HPB59-1	1					GENERAL TOLERANCE	
B	绝缘体	聚四氟乙烯	1				≥0~2<	±0.15	
A	主体	黄铜	1	镀金 / 镀镍	DESIGN	WANGGUIFA	2018.06.12	≥2~5<	±0.25
					CHECKED	ZHENGUILAN	2018.06.12	≥0~2<	±0.15
					APPROVED	LILIANJIANG	2018.06.14	≥5	±0.35

FIRST VIEW				The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM		TITLE::	
						SMA-KWE 20MM正脚4P 卧插	
SCALE				1:1	UNIT	mm	DWG NO: SMAKWE199-P030
PART NO: SMAKWE-2109209				MODEL NO: SMA-KWE-199-W4-X			
NAME:				SMA			
COAXIAL RF CONNECTOR							

SAMZO COMPONENTS

Electronic switch and connector manufacturer