




PCB LAYOUT

备注：侧弹分为外弹与内弹

目錄
MAPX

设变内容
MODIFICATION

日期
DATE

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000MΩ Min.

Contact Resistance:30 MΩ Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35°C to +85°C

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force: 3.5KG MAX

Unmating Force:0.7 KG MIN.

Contact finish:

01:Selective Gold Flash

02:Selective Gold 3U"

03:Selective Gold 5U"

04:Selective Gold 15U"

05:Selective Gold 30U"

产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.25	X'.	±5'
.X	±0.20	.X'	±2'
.XX	±0.15	.XX'	±1'
.XXX	±0.10	.XXX'	±0.5'

深圳市精拓金电子有限公司

单位
UNITS

MM

制图
DRAWING

尹先华

产品料号
PRODUCT PART NO.

903-341A2021S10200

比例
SCALE

1:1

审核
CHKD

郭志富

产品名称
PRODUCT NO.

AF无后盖短直脚8.6无边内弹
铁壳T型LCP黑胶SMT

日期
DATE

2013/11/02

核准
APPD

黄国荣

角法
VIEW

版本
VER

A0