

isc Silicon NPN Darlington Power Transistor

2STP535FP

DESCRIPTION

- With TO-220F packaging
- Very high DC current gain
- Monolithic darlington transistor with integrated antiparallel collector-emitter diode
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- AC-DC motor control
- Electronic ignition
- Alternator regulator

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	180	V
V_{CEO}	Collector-Emitter Voltage	180	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	8	A
I_{CM}	Collector Current-Peak	15	A
I_B	Base Current- Continuous	1	A
P_C	Collector Power Dissipation	37	W
T_j	Max.Junction Temperature	150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-65~150	$^{\circ}\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance,Junction to Case	3.4	$^{\circ}\text{C/W}$
$R_{th\ j-a}$	Thermal Resistance,Junction to Ambient	62.5	$^{\circ}\text{C/W}$



isc Silicon NPN Darlington Power Transistor**2STP535FP****ELECTRICAL CHARACTERISTICS****T_c=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V _{CEO(SUS)}	Collector-Emitter Sustaining Voltage	I _C = 30mA, I _B = 0	180		V
V _{CE(sat)1}	Collector-Emitter Saturation Voltage	I _C = 3A ,I _B = 6mA		2.0	V
V _{CE(sat)2}	Collector-Emitter Saturation Voltage	I _C = 8A ,I _B = 80mA		2.5	V
V _{BE(on)}	Base-Emitter On Voltage	I _C = 8A ; V _{CE} = 4V		2.8	V
I _{CBO}	Collector Cutoff Current	V _{CB} =180V, I _E = 0		50	μ A
I _{CEO}	Collector Cutoff Current	V _{CE} = 180V, I _B = 0		50	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0		100	μ A
h _{FE-1}	DC Current Gain	I _C = 3A ; V _{CE} = 4V	1000	20000	
h _{FE-2}	DC Current Gain	I _C = 8A ; V _{CE} = 4V	200		
V _F	Diode Forward Voltage	I _F =10A		2.8	V

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.