

isc N-Channel Mosfet Transistor

BUZ76

• FEATURES

- Drain Source Voltage-
: $V_{DS} = 400V(\text{Min})$
- Static Drain-Source On-Resistance
: $R_{DS(on)} = 1.8 \Omega (\text{Max})$
- Fast Switching Speed
- Low Drive Requirement
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

• DESCRIPTION



Designed for witched mode power supplies, motor control, welding, DC-DC & DC-AC converters, and in general purpose switching applications. switching regulators, switching converters.

• ABSOLUTE MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

SYMBOL	ARAMETER	VALUE	UNIT
V_{DS}	Drain-Source Voltage ($V_{GS}=0$)	400	V
V_{GS}	Gate-Source Voltage	± 20	V
I_D	Drain Current-continuous@ $TC=37^\circ\text{C}$	3	A
I_{DM}	Drain Current-Single Plused	12	A
P_{tot}	Total Dissipation@ $TC=25^\circ\text{C}$	40	W
T_j	Max. Operating Junction Temperature	150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th j-c}$	Thermal Resistance, Junction to Case	3.1	$^\circ\text{C/W}$
$R_{th j-a}$	Thermal Resistance, Junction to Ambient	75	$^\circ\text{C/W}$



isc N-Channel Mosfet Transistor**BUZ76****ELECTRICAL CHARACTERISTICS****T_C=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYPE	MAX	UNIT
V _{(BR)DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0; I _D =0.25mA	400			V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} ; I _D =1mA	2.1		4.0	V
V _{SD}	Diode Forward On-voltage	I _S = 6A; V _{GS} = 0			1.4	V
R _{DS(on)}	Drain-Source On-Resistance	V _{GS} = 10V; I _D = 2A			1.8	Ω
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V; V _{DS} = 0			±100	nA
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =400V; V _{GS} = 0			1	μA
G _{fs}	Forward Transconductance	V _{DS} = 25V; I _D =2A	2.1			S
t _{d(on)}	Turn-on Delay Time	V _{GS} =10V; I _D =2.5A; V _{DD} =30V; R _{GS} =50 Ω			12	ns
t _r	Rise Time				45	
t _{d(off)}	Turn-off Delay Time				75	
t _f	Fall Time				40	

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.