

isc Silicon PNP Power Transistors

D45H11

DESCRIPTION

- Low Collector-Emitter Saturation Voltage
: $V_{CE(sat)} = 1.0V(\text{Max}) @ I_C = 8A$
- Fast Switching Speeds
- Complement to Type D44H11
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS



- Designed for general pourpose power amplification and switching such as output or driver stages in applications such as switching regulators,converters and power amplifier.

ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CEO}	Collector-Emitter Voltage	-80	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current-Continuous	-10	A
I_{CM}	Collector Current-Peak	-20	A
P_C	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	50	W
T_J	Junction Temperature	-55~150	$^\circ\text{C}$
T_{stg}	Storage Temperature Range	-55~150	$^\circ\text{C}$

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	2.5	$^\circ\text{C}/\text{W}$
$R_{th\ j-a}$	Thermal Resistance,Junction to Ambient	75	$^\circ\text{C}/\text{W}$



isc Silicon PNP Power Transistors**D45H11****ELECTRICAL CHARACTERISTICS****T_C=25°C unless otherwise specified**

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = -8A ; I _B = -0.4 A			-1.0	V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = -8A ; I _B = -0.8 A			-1.5	V
I _{CES}	Collector Cutoff Current	V _{CE} =Rated V _{CEO} ; V _{BE} = 0			-10	μ A
I _{EBO}	Emitter Cutoff Current	V _{EB} = -5V; I _C = 0			-100	μ A
h _{FE-1}	DC Current Gain	I _C = -2A ; V _{CE} = -1V	60			
h _{FE-2}	DC Current Gain	I _C = -4A ; V _{CE} = -1V	40			
C _{OB}	Output Capacitance	V _{CB} = -10V, f= 1.0MHz		230		pF
f _T	Current-Gain—Bandwidth Product	I _C =-0.5A; V _{CE} =-10V; f _{test} =20MHz		40		MHz

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.