

Schottky Barrier Rectifier

STPS30M60SG

FEATURES



- With TO-263(D2PAK) packaging
- Low leakage current, low power loss, high efficiency
- High frequency operation
- High current capability
- Low stored charge majority carrier conduction
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Switching power supply
- High frequency inverters
- Freewheeling diodes
- Reverse battery protection
- Polarity protection applications

ABSOLUTE MAXIMUM RATINGS($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{RRM} V_{RMS} V_R	Peak Repetitive Reverse Voltage RMS Voltage DC Blocking Voltage	60	V
$I_{F(AV)}$	Average Rectified Forward Current @ $T_c=125^{\circ}\text{C}$	30	A
$I_{F(RMS)}$	Forward rms current	90	A
I_{FSM}	Nonrepetitive Peak Surge Current (10ms single half sine-wave superimposed on rated load conditions)	600	A
T_J	Junction Temperature	-65~150	$^{\circ}\text{C}$
T_{stg}	Storage Temperature Range	-65~175	$^{\circ}\text{C}$



Schottky Barrier Rectifier

STPS30M60SG

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	0.9	°C/W

ELECTRICAL CHARACTERISTICS (Pulse Test: Pulse Width=300 μ s, Duty Cycle $\leq$ 1%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
V_F	Maximum Instantaneous Forward Voltage	$I_F = 15A ; T_c = 25^\circ C$ $I_F = 15A ; T_c = 125^\circ C$ $I_F = 30A ; T_c = 25^\circ C$ $I_F = 30A ; T_c = 125^\circ C$	0.515 0.425 0.590 0.535	V
I_R	Maximum Instantaneous Reverse Current	$V_R = \text{rated } V_{RRM} ; T_c = 25^\circ C$ $V_R = \text{rated } V_{RRM} ; T_c = 125^\circ C$	0.165 100	mA

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.